



**Hikvision Value
Series DS-
2CD1163G2-
LIU(2.8MM)
Dome IP
security camera
Indoor &
outdoor 3200 x
1800 pixels
Ceiling**

Modelis: DS-2CD1163G2-LIU 2.8mm PL

Gamintojas: HIKVISION

EAN: 6942160472881

Prekės kodas: 572722

111.99€

Compliance certificates: UL | Compliance certificates: RoHS | Compliance certificates: CE |
Compliance certificates: REACH | Compliance certificates: WEEE | Compliance certificates: BIS |
Compliance certificates: CB | Number of Privacy masking areas: 4 | Package weight: 800 g |
Bluetooth: No | Package width: 150 mm | Maximum resolution: 3200 x 1800 pixels | Supported
graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 640 x 360 | Operating

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

temperature (T-T): -30 - 60 °C | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3200 x 1800 | Built-in light: Yes | Supported graphics resolutions: 1280 x 720 (HD 720) | Built-in microphone: Yes | Weight: 550 g | Supported graphics resolutions: 640 x 480 (VGA) | Package height: 141 mm | Mounting kit: Yes | Power consumption (max): 6 W | Ethernet LAN (RJ-45) ports: 1 | Power source type: DC, PoE | Form factor: Dome | Lens viewing angle, diagonal: 127° | Infrared (IR) cut-off filter: Yes | Number of languages: 1 | DC output voltage: 12 | Connectivity technology: Wired | Video recording: Yes | Heartbeat: Yes | Image quality adjustment: Saturation | Image quality adjustment: Sharpness | Placement supported: Indoor & outdoor | Number of sensors: 1 | Image quality adjustment: Contrast | Tilt angle range: 0 - 75° | Night vision: Yes | Lens viewing angle, vertical: 55° | Image quality adjustment: Brightness | Storage temperature (T-T): -30 - 60 °C | Mounting type: Ceiling | Number of lenses: 1 | Package depth: 150 mm | Number of users: 32 user(s) | Video motion detection: Yes | Privacy masking: Yes | Number of simultaneous live view channels: 6 channels | Product colour: White | Power consumption (Power over Ethernet (PoE)): 7.5 W | Mirror: Yes | Lens viewing angle, horizontal: 105° | Manual: Yes | Networking standards: IEEE 802.3af | Storage relative humidity (H-H): 0 - 95% | Bit rate range: 16 - 160 Kbit/s | Live view: Yes | Languages support: Polish | Type: IP security camera | Password protection: Yes | Operating relative humidity (H-H): 0 - 95% | DC output current: 0.5 A | Sample rates: 8 - 16 kHz | Infra-red wavelength: 850 nm | Dynamic range: 120 dB | Identify distance: 7 m | Minimum illumination: 0 lx | Ethernet interface type: Fast Ethernet | Back Light Compensation (BLC): Yes | LED type: IR/White | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP | Wi-Fi: No | Height: 97.6 mm | Ethernet LAN: Yes | IK code: IK08 | Number of cameras: 1 | Housing material: Plastic | Housing material: Metal | International Protection (IP) code: IP67 | Wide Dynamic Range (WDR): Yes | Night vision distance: 30 m | Audio formats supported: PCM | Day/night mode: Yes | Audio formats supported: G.722.1 | Sensor type: CMOS | Fixed focal length: 2.8 mm | Recognize distance: 15 m | Progressive scan: Yes | Audio formats supported: MP2L2 | Audio formats supported: G.711 μ-law | Video compression formats: H.264+ | Audio formats supported: G.711 A-law | Diameter: 12.1 cm | Detect distance: 76 m | Video compression formats: H.265 | Supported video modes: 480p | Supported video modes: 1080p | Total megapixels: 6 MP | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Built-in HDD: No | Video compression formats: H.265+ | Video compression formats: H.264 | Noise reduction: Yes | Supported video modes: 360p | Maximum aperture number: 1.6 | Audio formats supported: AAC-LC | Video formats supported: H.264+ | Video formats supported: H.265+ | Video formats supported: H.265 | Supported video modes: 720p | Supported video modes: 1440p | Signal-to-Noise Ratio (SNR): 52 dB | Frame rate: 20 fps | Observe distance: 30 m | Noise reduction technology: 3D noise reduction | Highlight Compensation (HLC): Yes | Angle of rotation:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

355° | Digital Wide Dynamic Range (DWDR): Yes | Video formats supported: H.264 | Camera shutter speed: 1/1000000 - 1/3 s | Pan range: 0 - 355° | HTTPS encryption: Yes | User access level: Administrator, Operator, User | Sustainability compliance: Yes | Password reset via email: Yes