



Reolink Fisheye Series P520 - 6MP Indoor Fisheye PoE Camera, 360 View, Multiple Display Modes, Person Detection

Modelis: P520

Gamintojas: REOLINK

EAN: 6975253984237

Prekės kodas: 572727

129.99€

Type: IP security camera | Card reader integrated: Yes | Mobile operating systems supported: Android | Networking standards: IEEE 802.3af | Product colour: Black | Mounting kit: Yes | Mobile operating systems supported: iOS | Video formats supported: H.265 | Product colour: Grey | Number of lenses: 1 | Maximum memory card size: 256 GB | Manual: Yes | DC output current: 1 A | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Power consumption (max): 12 W | Video motion detection: Yes | Mounting type: Ceiling/wall | Number of users: 20 user(s)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| LED type: IR | Bit rate: 64 Kbps - 8192 Kbps | Maximum resolution: 2560 x 2560 pixels | Built-in HDD: No | Weight: 293 g | Compatible memory cards: MicroSD (TransFlash) | Windows operating systems supported: Yes | Reset button: Yes | Power source type: DC, PoE | Placement supported: Indoor & outdoor | Built-in speaker(s): Yes | Frame rate: 25 fps | Fixed focal length: 1.98 mm | Height: 49.2 mm | Built-in microphone: Yes | Screws included: Yes | Night vision: Yes | Video recording: Yes | Total megapixels: 6.5 MP | Intelligent Video Surveillance (IVS) system features: Human detection | Operating temperature (T-T): -10 - 55 °C | Maximum aperture number: 2 | Video compression formats: H.265 | Ethernet LAN (RJ-45) ports: 1 | Number of cameras: 1 | DC-in jack: Yes | Form factor: Dome | Connectivity technology: Wired | Number of sensors: 1 | DC output voltage: 12, 48 | Night vision distance: 8 m | Optical sensor size: 25.4 / 2.5 mm (1 / 2.5") | Virtual assistant: Google Assistant | Ethernet LAN: Yes | Sensor type: CMOS | Mac operating systems supported: Yes | Live view: Yes | Supported network protocols: HTTPS, SSL, TCP/IP, UDP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P | Audio system: 2-way | Diameter: 12.6 cm | Infra-red wavelength: 850 nm | Infrared (IR) cut-off filter: Yes | Supported graphics resolutions: 2560 x 2560 | Lens viewing angle, vertical: 180° | User access level: Administrator, User | Lens viewing angle, horizontal: 180° | Lens viewing angle, diagonal: 180°