



Cudy GS108D network switch Unmanaged Gigabit Ethernet (10/100/1000) Black



Modelis: GS108D

Gamintojas: CUDY

EAN: 6971690790103

Prekės kodas: 572979

15.98€

Warnings: Do not open the case or try to repair it yourself. | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Operating temperature (T-T): 0 - 40 °C | Rack mounting: No | Power consumption (max): 2.75 W | Copper ethernet cabling technology: 10BASE-T | Power over Ethernet (PoE): No | Package type: Box | Copper ethernet cabling technology: 100BASE-TX | Forwarding rate: 11.904 Mpps | Package height: 63 mm | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Power connector: DC-in jack | Depth: 61.5 mm | DC input voltage: 5 V | Switching capacity: 16 Gbit/s | Jumbo frames support: Yes | Store-and-forward: Yes | Copper ethernet cabling technology: 1000BASE-T | Package width: 151 mm | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Weight:

89 g | Plug and Play: Yes | Width: 138 mm | Networking standards: IEEE 802.3u | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 90% | MAC address table: 8192 entries | Packet buffer memory: 0.5 MB | Operating relative humidity (H-H): 10 - 90% | Product colour: Black | LED indicators: Power | AC input voltage: 100 - 240 V | LED indicators: Link | Switch type: Unmanaged | Input current: 0.55 A | Cable types supported: Cat3 | Full duplex: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Package depth: 75 mm | Package weight: 210 g | Height: 24 mm | Ethernet LAN data rates: 10,100,1000 Mbit/s | Flow control support: Yes | LED indicators: Activity | Networking standards: IEEE 802.3az | Manual: Yes | Power source: DC | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage temperature (T-T): -40 - 70 °C | AC input frequency: 50/60 Hz | Power supply included: Yes | Cables included: DC | Jumbo frames: 15000 | Half duplex: Yes