



Keenetic Explorer 4G (KN- 4910) AC1200 Mesh Wi-Fi 5 4G Modem Router with a 4-Port Smart Switch

Modelis: KN-4910-01-EU

Gamintojas: KEENETIC

EAN: 4897082922155

Prekės kodas: 572982

117.99€

Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Intelligent Mesh technology: Yes | MU-MIMO technology: Yes | Number of guest networks (2.4 GHz): 7 | Bandwidth control: Yes | Number of guest networks (5 GHz): 7 | 4G data rate (max): 150 Mbit/s | Antenna design: External | Schedule access: Yes | PPPoE/PPTP/L2TP pass-through: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | SIM card slot: Yes | Guest access: Yes | WAN connection type: RJ-45, WISP | Ping check: Yes | Parental control: Yes | 3G standards: WCDMA | 3G bands supported: 900 | Command-line interface (CLI): Yes | Routing table: DHCP | 4G bands supported: 1900 | Mobile network generation: 4G | DoS attack prevention: Yes | Wi-Fi band: Dual-

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | WLAN data transfer rate (first band): 300 Mbit/s | SSID-based VLAN assignment: Yes | Traffic statistics: Yes | WireGuard: Yes | IPv4 & IPv6 features: IPv6 Telnet | 3G bands supported: 2100 MHz | IntelliQoS: Yes | System event log: Yes | 3G standards: HSDPA | HTTPS security for access via KeenDNS: Yes | 3G bands supported: 850 | Firewall: Yes | SIM card type: NanoSIM | 4G standard: LTE-TDD & LTE-FDD | Cloudflare DNS: Yes | AdGuard ad blocker: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Universal Plug and Play (UPnP): Yes | Short Message Service (SMS): Yes | 4G bands supported: 2300 | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 1800 | 4G bands supported: 900 | UDP-to-HTTP proxy: Yes | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | Number of users: 199 user(s) | WLAN data transfer rate (second band): 867 Mbit/s | 3G standards: HSUPA | Captive portal: Yes | Web-based setup wizard: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | WireGuard throughput: 45 Mbit/s | IGMP snooping: Yes | USSD request support: Yes | Switching protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Cloud-managed: Yes | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | Firewall security: SPI | Dynamic DNS (DDNS): Yes | Port triggering: Yes | L2TP/PPTP data rate: 95 Mbit/s | DHCP server: Yes | Port forwarding: Yes | 3G/4G USB modem compatibility: No | Policy-based routing: Yes | IPoE/PPPoE data rate: 95 Mbit/s | Internet connection backup: Yes | WPS push button: Yes | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 100 Mbit/s | Built-in processor: Yes | AC input frequency: 50/60 Hz | Output current: 1 A | Product colour: White | AC adapter included: Yes | Stateful Packet Inspection (SPI): Yes | Quick installation guide: Yes | MIMO: Yes | Quality of Service (QoS) support: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Product colour: Grey | Flash memory: 32 MB | Mobile operating systems supported: iOS | Cables included: LAN (RJ-45) | Height: 29 mm | Cabling technology: 10/100Base-T(X) | USB port: No | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Ethernet LAN interface type: Fast Ethernet | DHCP client: Yes | Depth: 110 mm | 3G: Yes | Backup function: Yes | Width: 159 mm | Processor frequency: 575 MHz | Weight: 236 g | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Product type: Tabletop router | Power source type: AC | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11a | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.1Q | WLAN data transfer rate (max): 1200 Mbit/s | Operating temperature (T-T): 0 - 40 °C | Internal memory: 128 MB | Ethernet LAN: Yes | Quick start guide: Yes | Processor model: MediaTek MT7628N | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Number of products included: 1 pc(s) | Networking standards: IEEE 802.11v | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11ac | Internal memory type: DDR2 | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.11b | Ethernet LAN (RJ-45) ports: 4 | Ethernet WAN: Yes | Security algorithms:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

WPA3-PSK | Antennas quantity: 4 | Processor manufacturer: MediaTek | Output voltage: 12 V |
Antenna connector type: SMA | LED indicators: LAN, Power, WLAN | Antenna gain level (max): 4 dBi |
Mobile operating systems supported: Android | Security algorithms: WPA2-Enterprise | Security
algorithms: OWE | Operating relative humidity (H-H): 20 - 95% | Antenna type: External | Network
address translation (NAT): Yes | Networking standards: IEEE 802.11k | Supported network protocols:
IPoE, PPPoE, PPTP, L2TP, 802.1x | Modem chipset: ASR1803S