

TP-Link TX401 tinklo plokštė Vidinis Eternetas 10000 Mbit/ai

Gamintojas: **TP-LINK** · Modelis: **TX401** · EAN: **6935364072827** · Prekės kodas: **573013**



96,90 €

Kaina su PVM

Be PVM: **80,08 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ PCI Express 3.0 Eternetas
- ✓ 2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Greitas eternetas, Gigabitinis eternetas 10000 Mbit/ai
- ✓ Vidinis Taikoma: PC



Aprašymas

Arm Your PC with the Latest 10G SpeedsArm Your PC with the Latest 10G Speeds

PCIe 3.0 Slot to 10 Gigabit Ethernet

Upgrade to 10G Networking

10 Gigabit Ethernet reaches blazing-fast data rates up to 10 billion bits per second—10× faster than standard Gigabit Ethernet. It's a brand-new era for all your bandwidth-intensive tasks from local data transfers to internet access.

10 Gbps Internet Access

Make Full Use of Your High-Speed Internet Access

10 Gbps NAS Connection

Lightning-Fast Local Data Transmissions

10 Gbps Host Server Building
High Hardware Configuration for a Powerful Server

Play Never Ends with 10G

With 10 Gbps internet access, your gaming will be fully optimized with a large boost in speed, latency, and responsiveness. Large-sized game downloads, seamless live streaming, and massive data backups via the cloud are as easy as choosing your character.

Local Data Transmissions in Seconds

For local connections, a 10G PCIe adapter helps build a lightning fast transport channel between a central server and other working machines in your local network. Local data transmissions will be a breeze for you as you handle bandwidth-intensive tasks easily at your home or office.

Versatile, Multi-Speed Compatibility

10GBase-T is backwards compatible with multiple data rates, including 10 Gbps, 5 Gbps, 2.5 Gbps, 1 Gbps, and 100 Mbps Base-T connectivity. The 10G Ethernet port automatically negotiates between higher and lower speed connections, allowing you to upgrade to 10G networking smoothly.

QoS Support

A Bandwidth Buff for Gaming

Quality of Service technology ensures enough bandwidth and avoids network congestion for PC gaming. It delivers prioritized performance for gamers.

Strengthened PCI Express 3.0 x4

Supports PCI Express Gen3 x4 for more efficient data transmissions

Easy Setup

Simple software installation with the intuitive Utility on the provided CD

Comprehensive System Support

Fully compatible with Windows 10/8.1/8/7, Windows Servers 2019/2016/2012 R2, Linux, and macOS.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	PCI Express
Sąsaja	Eternetas
Ethernet LAN (RJ-45) portų kiekis	1
PCI versija	3.0
Tinklas	
Didžiausias duomenų perdavimo greitis	10000 Mbit/ai
Tinklo standartai	IEEE 802.3, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Greitas eternetas, Gigabitinis eternetas

Eterneto LAN duomenų perdavimo norma 100,1000,2500,5000,10000 Mbit/ai

Konstrukcija

Vidinis	Taip
Taikoma	PC
Produkto spalva	Raudona
LED indikatoriai	Aktyvumas, Jungtis

Sistemos reikalavimai

Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Windows Server 2012 R2, Windows Server 2016, Windows Server 2019

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%

Svoris ir matmenys

Plotis	120,8 mm
Ilgis	98,2 mm
Aukštis	21,5 mm

Pakuotės duomenys

Pakuotės plotis	200 mm
Pakuotės gylis	150 mm
Pakuotės aukštis	44 mm
Paketo svoris	300 g

Pakuotės turinys

Pridėti kabeliai	LAN (RJ-45)
Pridėti montavimo kronšteinai	Taip
Šaltinis CD	Taip
Greito diegimo vadovas	Taip

Techninė informacija	
Atitikties sertifikatai	RoHS, Federalinė ryšių komisija (FCC), CE
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85176990
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	5,00cm × 16,00cm × 20,00cm
Svoris	0,30kg