



TP-Link TX401 network card Internal Ethernet 10000 Mbit/s

Modelis: TX401

Gamintojas: TP-LINK

EAN: 6935364072827

Prekės kodas: 573013

99.99€

PCI version: 3.0 | Package depth: 150 mm | Ethernet interface type: 5 Gigabit Ethernet | Package height: 44 mm | Interface: Ethernet | Ethernet interface type: Gigabit Ethernet | Host interface: PCI Express | Internal: Yes | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Ethernet interface type: 10 Gigabit Ethernet | Ethernet interface type: 2.5 Gigabit Ethernet | Mounting brackets included: Yes | Sustainability compliance: Yes | Linux operating systems supported: Yes | Depth: 98.2 mm | Width: 120.8 mm | Harmonized System (HS) code: 85176990 | Cables included: LAN (RJ-45) | Quick installation guide: Yes | Resource CD: Yes | Height: 21.5 mm | Server operating systems supported: Windows Server 2012 R2 | Server operating systems supported: Windows Server 2016 | Warnings: Please observe local regulations regarding the disposal of electronic waste. | Server operating systems supported: Windows Server 2019 | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Maximum data transfer rate: 10000 Mbit/s | Product colour: Red | LED indicators: Link | Windows operating

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Package weight: 300 g | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 10 x64 | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows 10 Education | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Ethernet LAN data rates: 10000 Mbit/s | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Component for: PC | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 7 | Ethernet LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 5000 Mbit/s | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Package width: 200 mm | Ethernet LAN data rates: 1000 | Operating temperature (T-T): 0 - 40 °C | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Ethernet LAN data rates: 2500 Mbit/s | Windows operating systems supported: Windows 10 Education x64 | LED indicators: Activity | Connectivity technology: Wired | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Ethernet LAN (RJ-45) ports: 1 | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3an | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3bz | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3x