



ASRock Z890 Pro RS - Motherboard

Modelis: Z890 Pro RS

Gamintojas: ASROCK

EAN: 4710483947452

Prekės kodas: 573457

215.99€

Ethernet LAN: Yes | Number of SATA III connectors: 4 | Audio chip: Realtek ALC897 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 1 | Motherboard chipset family: Intel | CPU fan connector: 2 | Line-out: Yes | Supported memory clock speed (max): 9066 MHz | USB 3.2 Gen 2x2 Type-C ports quantity: 1 | Memory slots type: DIMM | SPI TPM socket: 1 | Maximum internal memory: 256 GB | Supported memory types: DDR5 non-ECC | RGB LED pin header: Yes | Motherboard chipset: Intel Z890 | HDMI ports quantity: 1 | Supported storage drive interfaces: Blazing M.2 (PCIe Gen5 x4), Hyper M.2 (PCIe Gen4 x4) | Ethernet interface type: 2.5 Gigabit Ethernet | Motherboard form factor: ATX | Ethernet LAN (RJ-45) ports: 1 | BIOS type: UEFI AMI | Thunderbolt 4 ports quantity: 2 | Addressable LED connectors: 3 | ATX Power connector (24-pin): Yes | Number of USB 3.2 Gen 1 ports: 2 | Windows operating systems supported: Windows 11 x64 | Chassis fan connector (4-pin): 5 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | LAN controller: Dragon RTL8125BG | AIO pump fan connector: 1 | Processor manufacturer: Intel | MIC input: 1 | Operating system architecture: 64-bit | Compatible processor series: Intel Core Ultra (Series 2) | LED and speaker power socket: 1 | Audio output channels: 7.1 channels | Memory channels: Dual-channel | Flashback BIOS button: Yes | Number of memory slots: 4 | 8-pin power connector 12 V: 2 | External antenna connector: Yes, x 2 | Front panel

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

audio connector: Yes | DisplayPort 1.4: 1 | USB 2.0 connectors: 4 | USB 2.0 connectors: 2 | Speaker output: 1 | Processor socket: LGA 1851 (Socket V1) | Unbuffered memory: Yes | PCI Express x16 (Gen 5.x) slots: 1