



ASRock Z890M Riptide WiFi Motherboard



Modelis: Z890M Riptide WiFi

Gamintojas: ASROCK

EAN: 4710483949722

Prekės kodas: 573458

237.99€

Supported storage drive types: HDD & SSD | RAID support: Yes | Maximum number of SMP processors: 1 | Number of memory slots: 4 | DisplayPort version: 1.4 | Number of M.2 (M) slots: 1 | Number of SATA III connectors: 4 | Bluetooth: Yes | Motherboard chipset family: Intel | Supported storage drive interfaces: M.2, SATA III | Ethernet LAN: Yes | CPU fan connector: 2 | Line-out: Yes | ATX Power connector (24-pin): Yes | Width: 244 mm | Audio chip: Realtek ALC897 | TPM connector: Yes | Motherboard chipset: Intel Z890 | Depth: 244 mm | Supported memory types: DDR5 DIMM | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 2 | RAID levels: 0 | Ethernet interface type: 2.5 Gigabit Ethernet | HDMI ports quantity: 1 | Top Wi-Fi standard: Wi-Fi 6E (802.11ax) | Memory slots type: DIMM | Wi-Fi standards: 802.11ac | Motherboard form factor: micro ATX | Wi-Fi standards: 802.11b | RAID levels: 1 | Graphics card: Intel Xe LPG | Ethernet LAN (RJ-45) ports: 1 | Wi-Fi: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Intel® Turbo Boost Technology: 3.0 | Wi-Fi standards: 802.11g | USB 2.0 connectors: 2 | Wi-Fi standards: 802.11n | BIOS type: UEFI AMI | Wi-Fi standards: 802.11ax | Wi-Fi standards: 802.11ax | Maximum internal memory: 256 GB | Antennas quantity: 2 | Wi-Fi standards: 802.11a | Processor socket: LGA1851RL-ILM | Unbuffered memory: Yes | Windows operating systems supported: Windows 11 x64 | Audio output channels: 7.1 channels | RAID levels: 5

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| RAID levels: 10 | Memory channels: Dual-channel | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | LAN controller: Killer E3100G | Compatible processor series: Intel Core Ultra (Series 2) | Front panel audio connector: Yes | Processor manufacturer: Intel | Number of Thunderbolt 4 USB-C ports: 2 | Number of addressable LED slots: 2 | Chassis fan connector (4-pin): 3 | ECC compatibility: Non-ECC | Number of RGB LED pin headers: 1 | Thermistor Header: Yes | Bluetooth version: 5.3 | Pump connector: 1 | Memory speed (max): 9466 MHz | Wi-Fi antenna: Yes | Wi-Fi frequency: 2,4 Ghz / 5 GHz / 6 GHz | AIO pump fan connector: 1 | SPDIF optical output: Y | USB 2.0 Type-A ports quantity: 2 | Certificates: FCC | Certificates: CE | Certificates: ErP/EuP ready | Intel Extreme Memory Profile (XMP) version: 3.0 | 8-pin power connector 12 V: 2 | Cables included: Thermistor Cable x 1 | Wireless statistics: Yes | Number of microphone inputs: 1 | Cables included: SATA III 2 pcs. | Cables included: ARGB Splitter Cable x 1 | DisplayPort out quantity: 1 | Number of antenna connectors: 2 | PCI Express x16 (Gen 5.x) slots: 1 | Motherboard: Yes | Number of USB 3.2 Gen 2x2 (3.1 Gen 2x2) Type-C ports : 1