



Asrock B860M LiveMixer WiFi Intel B860 LGA 1851 (Socket V1) micro ATX

Modelis: B860M LiveMixer WiFi

Gamintojas: ASROCK

EAN: 4711581490314

Prekės kodas: 573460

172.99€

Number of SATA III connectors: 4 | Width: 244 mm | HDMI ports quantity: 1 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 6 | RGB LED pin header: Yes | On-board graphics card: Yes | Audio chip: Realtek ALC1220 | Motherboard chipset family: Intel | Wi-Fi: Yes | Microphone in: Yes | EPS power connector (8-pin): Yes | Motherboard chipset: Intel B860 | RAID levels: 10 | Number of storage drives supported: 7 | Audio output channels: 7.1 channels | RAID levels: 5 | RAID levels: 0 | Ethernet interface type: 2.5 Gigabit Ethernet | Maximum internal memory: 256 GB | S/PDIF out port: Yes | CPU fan connector: Yes | Front panel audio connector: Yes | RAID support: Yes | TPM connector: Yes | Number of chassis fan connectors: 3 | RAID levels: 1 | Bluetooth version: 5.3 | Motherboard form factor: micro ATX | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Number of memory slots: 4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Supported memory types: DDR5-SDRAM | Wi-Fi standards: 802.11g | Ethernet LAN (RJ-45) ports: 1 | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Memory slots type: DIMM | Supported storage drive interfaces: M.2, SATA III | Wi-Fi

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: Wi-Fi 6E (802.11ax) | Graphics card family: Intel | Bluetooth: Yes | Depth: 244 mm | Memory channels: Dual-channel | Windows operating systems supported: Windows 11 x64 | Number of M.2 (M) slots: 3 | Top Wi-Fi standard: Wi-Fi 6E (802.11ax) | Ethernet LAN: Yes | ATX Power connector (24-pin): Yes | Thunderbolt ports quantity: 1 | USB 3.2 Gen 2 (3.1 Gen 2) connectors: 1 | BIOS type: UEFI AMI | Processor socket: LGA 1851 (Socket V1) | USB 2.0 connectors: 2 | Unbuffered memory: Yes | Cables included: SATA | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | LAN controller: Dragon RTL8125BG | USB 2.0 ports quantity: 6 | Processor manufacturer: Intel | ECC compatibility: Non-ECC | Number of RGB LED pin headers: 5 | Number of CPU fan connectors: 2 | Number of EPS power connectors (8-pin): 2 | PCI Express x16 (Gen 5.x) slots: 1 | Warnings: Do not open or modify the motherboard to prevent damage. | Warnings: In case of installation problems, contact a qualified service technician. | PCI Express x4 (Gen 4.x) slots: 1 | Warnings: When disposing of the product, follow local regulations for the recycling of electronics.