



Dahua Technology VTO2202F-P-S3 video intercom system 2 MP Silver

Modelis: VTO2202F-P-S3

Gamintojas: DAHUA

EAN: 6923172563194

Prekės kodas: 573517

141.99€

Certification: CE, FCC, UL | RS-485 ports (transmitter): 1 | IK code: IK07 | Operating system installed: Embedded LINUX | Built-in speaker(s): Yes | Speakerphone: Yes | Connectivity technology: Wired | Ethernet LAN data rates: 100 | Proper use: Outdoor | Operating temperature (T-T): -30 - 60 °C | Maximum frame rate: 25 fps | Ethernet LAN (RJ-45) ports: 1 | Field of view (FOV) angle: 176.7° | Ethernet LAN data rates: 10 | Optical sensor size: 25.4 / 2.9 mm (1 / 2.9") | Cabling technology: 10/100Base-T(X) | LED type: IR | Indoor unit included: No | Built-in microphone: Yes | Night vision: Yes | Control type: Buttons | Number of speakers: 1 | Maximum memory card size: 256 GB | Outdoor unit power type: DC/PoE | Product colour: Silver | Viewing angle, vertical: 87.1° | Power consumption (typical): 5 W | Wall mountable: Yes | Megapixel (approx.): 2 MP | Quantity per pack: 1 pc(s) | Depth: 28.5 mm | Power consumption (standby): 4 W | Wide Dynamic Range (WDR): Yes | International Protection (IP) code: IP65 | Storage temperature (T-T): 0 - 40 °C | Placement supported: Vertical |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Sensor type: CMOS | Door station control: Yes | Compatible memory cards: MicroSD (TransFlash) | Viewing angle, horizontal: 168.6° | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Width: 96 mm | Height: 130 mm | Supported network protocols: IPv4 RTSP UDP DNS P2P UPnP RTP TCP SIP | Power over Ethernet (PoE): Yes | Voice codecs: G.711a | Web-based management: Yes | Housing material: Aluminium | Video formats supported: H.265 | Streaming capability: Yes | Voice codecs: PCM | Outdoor unit included: Yes | Video formats supported: H.264 | Voice codecs: G.711u | Package weight: 480 g