

Asrock PRO-M1000G 1000W 80 PLUS Gold power supply unit

Gamintojas: **ASROCK** · Modelis: **PRO-M1000G** · EAN: **4711581493087** · Prekės kodas: **573746**



127,90 €

Kaina su PVM

Be PVM: **105,70 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

PCI Express power connectors (12+4 pin): 1 | Product colour: Black | AC input frequency: 50/60 Hz | AC input voltage: 100 - 240 V | Input current: 15-8 A | Number of SATA power connectors: 8 | Height: 86 mm | Peripheral (Molex) power connectors (4-pin): 4 | Combined power (-12V): 3.6 W | Depth: 150 mm | Power protection features: OCP | PCI Express power connectors (6+2 pin): 3 | Power protection features: OTP | Max output current (+12V): 83.3 A | Motherboard power cable length: 60 cm | Max output current (+3.3V): 20 A | Combined power (+5V): 120 W | Combined power (+3.3V): 120 W | Power protection features: UVP | Power protection features: OVP | Max output current (+5Vsb): 3 A | Mean time between failures (MTBF): 100000 h | 80 PLUS certification: 80 PLUS Gold | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | Power supply unit (PSU) form factor: ATX | Power protection features: OPP | Power protection features: SCP | Cooling type: Active | ATX version: 3.1 | Fan diameter: 13.5 cm | Max output current (-12V): 0.3 A | Width: 150 mm | Motherboard power connector: 24-pin ATX | Combined power (+12V): 1000 W | Power protection features: SIP | Number of fans: 1 fan(s) | CPU power connector (4+4 pin): Yes | EPS power connector (4+4 pin): Yes | Total power: 1000 W | Purpose: PC

Techninė specifikacija

Specifications

Sandėlio grupė

Power supplies for enclosures [+0][-0]

Matmenys ir svoris

Matmenys (I × P × A)

21,00cm × 14,00cm × 31,00cm

Svoris

2,90kg