



Asrock PRO-M750G 750W 80 PLUS Gold power supply unit

Modelis: PRO-M750G

Gamintojas: ASROCK

EAN: 4711581493001

Prekės kodas: 573748

94.99€

Width: 150 mm | Combined power (+5V): 120 W | Cooling type: Active | Height: 86 mm | Max output current (+3.3V): 20 A | Power protection features: UVP | Max output current (+12V): 62.5 A | Combined power (+3.3V): 120 W | Motherboard power cable length: 60 cm | Power protection features: OPP | Power protection features: SCP | Total power: 750 W | Power protection features: OTP | Power supply unit (PSU) form factor: ATX | Product colour: Black | Power protection features: SIP | Motherboard power connector: 24-pin ATX | ATX version: 3.1 | Fan diameter: 13.5 cm | Depth: 150 mm | Power protection features: OCP | Purpose: PC | Power protection features: OVP | Combined power (+12V): 750 W | Combined power (+5Vsb): 15 W | EPS power connector (4+4 pin): Yes | Max output current (+5V): 20 A | AC input voltage: 100 - 240 V | 80 PLUS certification: 80 PLUS Gold | Input current: 10 - 5 A | AC input frequency: 50/60 Hz | Number of fans: 1 fan(s) | Combined power (-12V): 3.6 W | Number of SATA power connectors: 4 | Max output current (+5Vsb): 3 A | Peripheral (Molex) power connectors (4-pin): 4 | Mean time between failures (MTBF): 100000 h | PCI Express

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

power connectors (6+2 pin): 3 | Max output current (-12V): 0.3 A | CPU power connector (4+4 pin):
Yes | PCI Express power connectors (12+4 pin): 1