



Chieftec Core BBS-600S power supply unit 600 W 24-pin ATX PS/2 Black



Modelis: BBS-600S

Gamintojas: CHIEFTEC

EAN: 753263076137

Prekės kodas: 573758

76.99€

Depth: 150 mm | Power supply unit (PSU) form factor: PS/2 | Height: 86 mm | AC input frequency: 47 - 63 Hz | Product colour: Black | Power protection features: Overload | Width: 140 mm | Total power: 600 W | Peripheral (Molex) power connectors (4-pin): 3 | PCI Express power connectors (6+2 pin): 2 | Power protection features: Short circuit | Power protection features: Over voltage | Harmonized System (HS) code: 84733020 | Fan diameter: 12 cm | Package weight: 2.08 kg | Number of fans: 1 fan(s) | Cabling type: Non-Modular | AC input voltage: 100 - 240 V | Input current: 9 A | Weight: 1.67 kg | 80 PLUS certification: 80 PLUS Gold | Combined power (-12V): 3.6 W | Cooling type: Active | SATA power cable length: 500 mm | Motherboard power cable length: 65 cm | Max output current (+12V1): 49 A | SATA power cable length: 150 mm | Max output current (+3.3V): 20 A | Purpose: PC | Power Factor Correction (PFC) type: Active | Combined power (+5Vsb): 12.5 W | Max output current (-12V): 0.3 A | Max output current (+5V): 20 A | Warnings: Avoid contact of the product with water or other liquids. | Warnings: Do not open the case - risk of electric shock. | Warnings: The product is not

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

suitable for disposal with municipal waste - dispose of in accordance with local regulations. | CPU power cable length: 65 cm | Floppy drive power connector: 1 | PCI Express power cable length: 50 cm | Number of SATA power connectors: 6 | Motherboard power connector: 24-pin ATX | Peripheral (Molex) power cable length: 500 mm | CPU power connector (4+4 pin): Yes | Max output current (+5Vsb): 2.5 A | Peripheral (Molex) power cable length: 150 mm