



Power supply Chieftec EON ZPU-600S 600W



Modelis: ZPU-600S

Gamintojas: CHIEFTEC

EAN: 753263078438

Prekės kodas: 573760

51.99€

AC input frequency: 50 - 60 Hz | Power supply unit (PSU) form factor: ATX | Number of SATA power connectors: 4 | Max output current (+5Vsb): 2.5 A | On/off switch: Yes | Peripheral (Molex) power cable length: 150 | Hazard pictogram(s): GHS09: Environmental hazard | Depth: 140 mm | Fan location: Top | Weight: 1.34 kg | Motherboard power cable length: 65 cm | Peripheral (Molex) power cable length: 450 mm | Width: 150 mm | Total power: 600 W | 80 PLUS certification: 80 PLUS | EPS power connector (4+4 pin): 2 | Cooling type: Active | PCI Express power connectors (6+2 pin): 2 | SATA power cable length: 450 mm | AC input voltage: 200 - 240 V | Hazard pictogram(s): GHS02: Flammable | Hazard pictogram(s): GHS07: Harmful | SATA power cable length: 150 | Length of EPS power connectors (4+4 pin) : 70 cm | Power protection features: OVP (overvoltage protection) | Peripheral (Molex) power connectors (4-pin): 2 | Power protection features: SCP (short circuit protection) | Max output current (+3.3V): 20 A | Power protection features: UVP (undervoltage protection) | Power protection features: AFC (automatic fan speed control) | Product colour: Black | Max output current (+5V): 20 A | Fan diameter: 12 cm | ATX version: 2.3 | Motherboard power connector: 20+4 pin ATX | Power protection features: OPP (overload protection) | Power protection features: SIP (surge and shock protection) | Number of fans: 1 fan(s) | PCI Express power cable

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

length: 55 cm | Package weight: 1.62 kg | Backlight: No | Max output current (+12V): 45 A | Modular cabling : No | Height: 86 mm | Power Factor Correction (PFC) type: Active | Max output current (-12V): 0.4 A