



Chieftec Smart GPF-400P power supply unit 400 W 20+4 pin ATX TFX Grey

Modelis: GPF-400P

Gamintojas: CHIEFTEC

EAN: 753263076809

Prekės kodas: 573776

44.99€

Product colour: Grey | Power supply unit (PSU) form factor: TFX | Fan diameter: 8 cm | Height: 65 mm | Purpose: PC/Server | Package weight: 1.13 kg | Power protection features: Overheating | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Overload | Power protection features: Under voltage | AC input frequency: 47 - 63 Hz | Cooling type: Active | Total power: 400 W | Weight: 1.07 kg | Width: 85 mm | ATX version: 2.3 | Cabling type: Non-Modular | Number of fans: 1 fan(s) | Efficiency: 85% | Power factor: 0.9 | Depth: 175 mm | Peripheral (Molex) power connectors (4-pin): 2 | Combined power (-12V): 3.6 W | SATA power cable length: 150 | Combined power (+5V): 105 W | Floppy disk drive cable length: 15 cm | Max output current (+12V2): 17 A | Max output current (+12V1): 17 A | Input current: 6.3 A | Number of SATA power connectors: 4 | AC input voltage: 100 - 240 V | CPU power cable length: 35 cm | Motherboard power connector: 20+4 pin ATX | SATA power cable length: 350 | Motherboard power cable length: 30 cm | Peripheral (Molex) power cable length: 350 | Max output current (+5Vsb): 2 A |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Peripheral (Molex) power cable length: 150 | Max output current (+3.3V): 16 A | Floppy drive power connector: 1 | Compliance certificates: Federal Communications Commission (FCC) | Max output current (-12V): 0.3 A | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: EAC | Combined power (+3.3V): 105 W | Combined power (+5Vsb): 10 W | Power Factor Correction (PFC) type: Active | Max output current (+5V): 18 A | EPS power connector (4+4 pin): Yes | Combined power (+12V): 336 W