



ENDORFY Vero L6 power supply unit 650 W 24- pin ATX ATX Black



Modelis: EY7A015

Gamintojas: ENDORFY

EAN: 5903018668918

Prekės kodas: 573795

72.00€

Doesn't contain: Lead | Doesn't contain: Mercury | EPS power connector (4+4 pin): Yes | Doesn't contain: Cadmium | Warranty period: 5 year(s) | Max output current (+5Vsb): 3 A | Motherboard power connector: 24-pin ATX | Waste Electrical and Electronic Equipment (WEEE) compliance: Yes | Peripheral (Molex) power cable length: 800 mm | Number of SATA power connectors: 5 | Max output current (+5V): 20 A | PCI Express power connectors (16-pin): 1 | Height: 87 mm | ATX Power connector (24-pin): Yes | On/off switch: Yes | Depth: 140 mm | Manual: Yes | AC input voltage: 200 - 240 V | Power protection features: Overheating | Package depth: 220 mm | Number of fans: 1 fan(s) | Product colour: Black | Cables included: AC | Package weight: 2.09 kg | AC input frequency: 50 Hz | Peripheral (Molex) power connectors (4-pin): 1 | Package width: 273 mm | Weight: 1.57 kg | Width: 150 mm | Cooling type: Active | 80 PLUS certification: 80 PLUS Bronze | Power protection features: Over power | Input current: 5 A | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power protection features: Surge & inrush protection (SIP) | Package height: 100 mm | Mean time between failures (MTBF): 80000 h | Combined power (+5Vsb): 15 W | PCI Express power connectors (6+2 pin): 2 | Total power: 650 W | Combined power (+5V): 100 W | Max output current (+12V): 54 A | SATA power cable length: 800 | Max output current (+3.3V): 20 A | Power Factor Correction (PFC) type: Active | Bearing technology: FDB | Combined power (+3.3V): 100 W | Power supply unit (PSU) form factor: ATX | Fan diameter: 12 cm | SATA power cable length: 500 mm | ATX version: 3.1 | Combined power (+12V): 648 W | Motherboard power cable length: 57 cm | Purpose: PC | Cabling type: Non-Modular | Illumination: No | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: UKCA | Compliance certificates: CCC