



GIGABYTE P750BS Power Supply - PCI-E 6+2 Pin x 4, 80 PLUS Bronze, 120mm Fan, ATX compatible, EU Plug

Modelis: GP-P750BS

Gamintojas: GIGABYTE

EAN: 4719331555238

Prekės kodas: 573800

63.98€

Floppy disk drive connector: Yes | Depth: 140 mm | Width: 150 mm | Weight: 2.22 kg | Efficiency: 88% | Power factor: 0.9 | Total power: 750 W | Package depth: 206 mm | Product colour: Black | Package type: Box | AC input voltage: 200 - 240 V | Input current: 6 A | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Height: 86 mm | Package height: 117 mm | AC input frequency: 50/60 Hz | On/off switch: Yes | Peripheral (Molex) power connectors (4-pin): 2 | Purpose: PC | Number of fans: 1 fan(s) | Package weight: 2.68 kg | Package width: 254 mm | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Overheating | Power protection features: Over power | Fan diameter: 12 cm | Cooling type:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Active | Power protection features: Under voltage | Power protection features: Over current | Max output current (+3.3V): 20 A | Floppy drive power connector: 2 | Combined power (+5V): 100 W | Max output current (+5Vsb): 3 A | ATX power connector (20+4 pin): Yes | PCI Express power connectors (6+2 pin): 4 | Power Good signal delay range: 100 - 150 ms | SATA power cable length: 500 mm | Motherboard power cable length: 60 cm | SATA power cable length: 150 mm | Motherboard power connector: 20+4 pin ATX | PCI Express connector: Yes | Peripheral (Molex) power cable length: 150 mm | Bearing technology: FDB | Peripheral (Molex) power cable length: 600 | Combined power (-12V): 3.6 W | Number of SATA power connectors: 7 | Combined power (+5Vsb): 15 W | CPU power connector (4+4 pin): Yes | Max output current (+5V): 20 A | Fan location: Top | Max output current (+12V): 62.5 A | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 100 W | Power supply unit (PSU) form factor: ATX | Hold time: 16 ms | Max output current (-12V): 0.3 A | Combined power (+12V): 750 W | Cabling type: Non-Modular | Warranty period: 3 year(s)