



XPG CORE REACTOR II 1200W Power Supply



Modelis: 75261221

Gamintojas: XPG

EAN: 4711085942401

Prekės kodas: 573807

151.00€

Certification: CE | CB | FCC(IC) | TUV | cTUVus | TUV S-Zeichen | NOM | BSMI | UKCA | EAC | CCC | RCM
| ATX power connector (12+4 pin): Yes | EPS power connector (8-pin): Yes | Power protection
features: Under voltage | Power protection features: Over current | Power protection features: Over
power | Depth: 150 mm | Total power: 1200 W | Power protection features: Short circuit | Power
protection features: Over voltage | Fan diameter: 13.5 cm | Power protection features: Overheating |
Power protection features: Surge & inrush protection (SIP) | Product colour: Black | AC input
frequency: 50/60 Hz | Package depth: 338 mm | Package weight: 3.43 kg | AC input voltage: 100 -
240 V | Input current: 15 A | 80 PLUS certification: 80 PLUS Gold | Peripheral (Molex) power
connectors (4-pin): 3 | Purpose: PC | Package width: 210 mm | Power factor: 0.99 | Width: 160 mm |
Package height: 157 mm | ATX Power connector (24-pin): Yes | Height: 86 mm | Max output current
(+5V): 22 A | Max output current (+3.3V): 22 A | Warnings: Avoid contact of the product with water
or other liquids. | Max output current (+12V): 100 A | Warnings: Do not open the case - risk of
electric shock. | Warnings: The product is not suitable for disposal with municipal waste - dispose of
in accordance with local regulations. | Power supply unit (PSU) form factor: ATX | Mean time between

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

failures (MTBF): 100000 h | Bearing technology: FDB | Compliance certificates: UKCA | EPS version: 2.92 | Number of SATA power connectors: 9 | PCI Express power connectors (6+2 pin): 8 | Max output current (+5Vsb): 3 A | ATX version: 3.0 | Cabling type: Fully-Modular | Compliance certificates: CE | Compliance certificates: China Compulsory Certification (CCC) | Compliance certificates: Norma Oficial Mexicana (NOM) | Compliance certificates: RCM | Max output current (-12V): 0.3 A | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: cTUVus | Compliance certificates: CB | Compliance certificates: EAC | Compliance certificates: BSMI | Motherboard power connector: 24-pin ATX