



XPG CORE REACTOR II 1000W Power Supply



Modelis: 75261209

Gamintojas: XPG

EAN: 4711085942395

Prekės kodas: 573808

151.99€

ATX power connector (12+4 pin): Yes | Warnings: The product is not suitable for disposal with municipal waste - dispose of in accordance with local regulations. | Compliance certificates: BSMI | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: cTUVus | Warnings: Avoid contact of the product with water or other liquids. | Compliance certificates: RCM | Compliance certificates: Norma Oficial Mexicana (NOM) | Warnings: Do not open the case - risk of electric shock. | Compliance certificates: CE | Compliance certificates: China Compulsory Certification (CCC) | Compliance certificates: UKCA | Compliance certificates: CB | Compliance certificates: EAC | AC input frequency: 50/60 Hz | Depth: 150 mm | Cooling type: Active | Package width: 210 mm | ATX Power connector (24-pin): Yes | Peripheral (Molex) power connectors (4-pin): 3 | Package height: 157 mm | Width: 160 mm | Height: 86 mm | EPS power connector (8-pin): Yes | AC input voltage: 100 - 240 V | Input current: 13 A | Package weight: 3.43 kg | Number of fans: 1 fan(s) | 80 PLUS certification: 80 PLUS Gold | Weight: 1.77 kg | Power protection features: Short circuit | Package depth: 338 mm | Product colour: Black | Total power: 1000 W | Power factor: 0.99 |

Motherboard power connector: 24-pin ATX | Max output current (-12V): 0.3 A | Cabling type: Fully-

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Modular | ATX version: 3.0 | Fan diameter: 13.5 cm | Power protection features: Over power | Power protection features: Overheating | Max output current (+12V): 83.5 A | Power protection features: Surge & inrush protection (SIP) | Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Number of SATA power connectors: 9 | EPS version: 2.92 | Purpose: PC | PCI Express power connectors (6+2 pin): 8 | Max output current (+3.3V): 22 A | Max output current (+5Vsb): 3 A | Mean time between failures (MTBF): 100000 h | Max output current (+5V): 22 A | Bearing technology: FDB | Power supply unit (PSU) form factor: ATX