



XPG COREREACTOR II VE 850W Power Supply



Modelis: 75261435

Gamintojas: XPG

EAN: 4711085946256

Prekės kodas: 573810

114.99€

Certification: CB / CE / FCC / TUV / cTUVus / BSMI / CCC NOM / FCC IC / UKCA / TUV / TUV S-Mark / cTUVus | Bearing technology: FDB | SATA power cable length: 450 | Max output current (+5Vsb): 3 A | Depth: 140 mm | ATX version: 3.1 | Cabling type: Fully-Modular | Motherboard power connector: 24-pin ATX | Mean time between failures (MTBF): 100000 h | EPS power connector (8-pin): Yes | Height: 86 mm | Total power: 850 W | ATX power connector (12+4 pin): Yes | SATA power cable length: 150 mm | Power supply unit (PSU) form factor: ATX | Max output current (+12V): 70.8 A | EPS power connector (4+4 pin): Yes | Power factor: 0.99 | Max output current (+5V): 20 A | Purpose: PC | CPU power connector (4+4 pin): Yes | Motherboard power cable length: 65 cm | 80 PLUS certification: 80 PLUS Gold | Number of fans: 1 fan(s) | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Surge & inrush protection (SIP) | Power protection features: Overheating | Max output current (-12V): 0.3 A | Fan diameter: 12 cm | Power protection features: Over power | PCI Express power connectors (6+2 pin): 3 | Number of SATA power connectors: 6 | Max output current (+3.3V): 20 A | Width: 150 mm | CPU power cable length: 75 cm | PCI Express

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

power connectors (12+4 pin) cable length: 600 mm | Warnings: Do not open the case - risk of electric shock. | Warnings: Avoid contact of the product with water or other liquids. | Warnings: The product is not suitable for disposal with municipal waste - dispose of in accordance with local regulations. | PCI Express power connectors (12-pin): 1 | AC input voltage: 100 - 240 V | Cooling type: Active | ATX Power connector (24-pin): Yes | Input current: 12 A | Peripheral (Molex) power connectors (4-pin): 2 | Package weight: 3.03 kg | AC input frequency: 47 - 63 Hz | Weight: 1.45 kg | Product colour: Black