



XPG CORE REACTOR II VE 750W Power Supply



Modelis: 75261424

Gamintojas: XPG

EAN: 4711085946249

Prekės kodas: 573811

98.99€

Certification: CB / CE / FCC / TUV / cTUVus / BSMI / CCC NOM / FCC IC / UKCA / TUV / TUV S-Mark / cTUVus | Depth: 140 mm | Height: 86 mm | Number of fans: 1 fan(s) | Power protection features: Surge & inrush protection (SIP) | Power protection features: Overheating | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | 80 PLUS certification: 80 PLUS Gold | ATX power connector (12+4 pin): Yes | PCI Express power connectors (12+4 pin) cable length: 600 mm | Max output current (+12V): 62.5 A | Power factor: 0.99 | Warnings: Do not open the case - risk of electric shock. | SATA power cable length: 450 | SATA power cable length: 150 mm | Purpose: PC | PCI Express power connectors (6+2 pin): 3 | Bearing technology: FDB | Max output current (+5Vsb): 3 A | CPU power cable length: 75 cm | Number of SATA power connectors: 6 | Total power: 750 W | Warnings: Avoid contact of the product with water or other liquids. | CPU power connector (4+4 pin): Yes | Cabling type: Fully-Modular | Warnings: The product is not suitable for disposal with municipal waste - dispose of in accordance with local regulations. | Motherboard power cable length: 65 cm | Power supply unit (PSU) form factor: ATX |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Mean time between failures (MTBF): 100000 h | Max output current (+3.3V): 20 A | Max output current (+5V): 20 A | Motherboard power connector: 24-pin ATX | Fan diameter: 12 cm | ATX version: 3.1 | Max output current (-12V): 0.3 A | Width: 150 mm | Input current: 10 A | Package weight: 3.03 kg | AC input voltage: 100 - 240 V | EPS power connector (8-pin): Yes | AC input frequency: 47 - 63 Hz | Weight: 1.45 kg | Cooling type: Active | Product colour: Black | Peripheral (Molex) power connectors (4-pin): 2