



Emergency power supply Armac UPS OFFICE LINE- INTERACTIVE O/650E/LCD

Modelis: O/650E/LCD

Gamintojas: ARMAC

EAN: 5901969406580

Prekės kodas: 573822

82.99€

AC outlet types: Type E | Operating relative humidity (H-H): 10 - 90% | Output power capacity: 650 VA | Depth: 305 mm | UPS topology: Line-Interactive | Power protection features: Short circuit | Width: 85 mm | Battery technology: Maintenance Free, Lead Acid (AGM) | Output voltage: 230 V | Cold start: Yes | Typical backup time at full load: 3 min | USB port: Yes | Automatic battery test: Yes | Auto-restart: Yes | Output power: 390 W | Output frequency: 50 Hz | Response time: 2 - 6 ms | Output operation voltage (min): 255 V | Battery voltage: 12 V | USB cable included: No | Power protection features: Battery discharge | Battery capacity: 7 Ah | Typical backup time at half load: 20 min | Battery recharge time (90%): 6 h | RJ-45 ports quantity: 2 | Form factor: Tower | Waveform: Sine | Noise level: 45 dB | Automatic Voltage Regulation (AVR): Yes | Power protection features: Overvoltage protection | AC outlets quantity: 2 AC outlet(s) | Operating temperature (T-T): 0 - 45 °C |

Product colour: Black | Input frequency: 45 - 65 Hz | Number of batteries supported: 1 | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

protection features: Over power | Power protection features: Input fuse | Built-in display: LCD |
Weight: 4.6 g | Height: 141 mm | Output operation voltage (max): 195 V | Input operation voltage
(min): 145 V | Input operation voltage (max): 290 V