



Emergency power supply Armac UPS OFFICE LINE- INTERACTIVE O/850E/LCD

Modelis: O/850E/LCD

Gamintojas: ARMAC

EAN: 5901969406597

Prekės kodas: 573823

96.99€

AC outlets quantity: 2 AC outlet(s) | Power protection features: Overvoltage protection | Typical backup time at full load: 3 min | Power protection features: Short circuit | Power protection features: Battery discharge | Output power capacity: 850 kVA | Depth: 305 mm | UPS topology: Line-Interactive | AC outlet types: Type E | Power protection features: Over power | Power protection features: Input fuse | Cold start: Yes | Input frequency: 45 - 65 Hz | Width: 85 mm | Response time: 2 - 6 ms | Battery recharge time (90%): 6 h | Operating temperature (T-T): 0 - 45 °C | USB port: Yes | RJ-45 ports quantity: 2 | USB cable included: No | Product colour: Black | Weight: 5.5 kg | Output operation voltage (max): 195 V | Input operation voltage (min): 145 V | Input operation voltage (max): 290 V | Auto-restart: Yes | Output power: 480 W | Automatic battery test: Yes | Automatic Voltage Regulation (AVR): Yes | Output voltage: 230 V | Battery technology: Maintenance Free, Lead Acid (AGM) | Operating relative humidity (H-H): 10 - 90% | Battery capacity: 9 Ah | Form factor:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Tower | Waveform: Sine | Height: 141 mm | Output operation voltage (min): 255 V | Built-in display: LCD | Noise level: 45 dB | Typical backup time at half load: 20 min | Battery voltage: 12 V | Output frequency: 50 Hz | Number of batteries supported: 1