

Emergency power supply Armac UPS OFFICE LINE-INTERACTIVE O/1500F/LCD

Gamintojas: **ARMAC** · Modelis: **O/1500F/LCD** · EAN: **5901969406658** · Prekės kodas: **573825**



137,90 €

Kaina su PVM

Be PVM: **113,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Response time: 2 - 6 ms | Operating temperature (T-T): 0 - 45 °C | Weight: 11.2 kg | Noise level: 45 dB | Width: 120 mm | Built-in display: LCD | AC outlets quantity: 3 AC outlet(s) | Battery capacity: 9 Ah | Battery technology: Maintenance Free, Lead Acid (AGM) | Battery voltage: 12 V | Product colour: Black | Number of batteries supported: 2 | Operating relative humidity (H-H): 10 - 90% | Output power: 950 W | Form factor: Tower | Output frequency: 50 Hz | USB port: Yes | Typical backup time at half load: 20 min | Input frequency: 45 - 65 Hz | Output operation voltage (min): 255 V | Depth: 350 mm | UPS topology: Line-Interactive | Automatic Voltage Regulation (AVR): Yes | Output operation voltage (max): 195 V | Height: 188 mm | Cold start: Yes | Automatic battery test: Yes | AC outlet types: Type F | Battery recharge time (90%): 6 h | Output power capacity: 1500 kVA | Output voltage: 230 V | Waveform: Sine | RJ-45 ports quantity: 2 | USB cable included: No | Input operation voltage (min): 145 V | Input operation voltage (max): 290 V | Auto-restart: Yes | Power protection features: Overvoltage protection | Power protection features: Short circuit | Power protection features: Over power | Power protection features: Input fuse | Power protection features: Battery discharge | Typical backup time at full load: 3 min

Techninė specifikacija

Specifications

Sandėlio grupė

UPS power supplies [+0][-0]

Matmenys ir svoris

Matmenys (I × P × A)	30,00cm × 40,00cm × 20,00cm
Svoris	11,65kg