



Emergency power supply Armac UPS OFFICE LINE- INTERACTIVE O/1500F/LCD

Modelis: O/1500F/LCD

Gamintojas: ARMAC

EAN: 5901969406658

Prekės kodas: 573825

155.99€

Typical backup time at half load: 20 min | Input frequency: 45 - 65 Hz | Noise level: 45 dB | Battery technology: Maintenance Free, Lead Acid (AGM) | Operating relative humidity (H-H): 10 - 90% | Output voltage: 230 V | Battery capacity: 9 Ah | Number of batteries supported: 2 | Width: 120 mm | Product colour: Black | Automatic battery test: Yes | Auto-restart: Yes | Height: 188 mm | USB cable included: No | Operating temperature (T-T): 0 - 45 °C | Output power: 950 W | Output operation voltage (max): 195 V | Cold start: Yes | Automatic Voltage Regulation (AVR): Yes | Built-in display: LCD | AC outlets quantity: 3 AC outlet(s) | USB port: Yes | Power protection features: Short circuit | Power protection features: Battery discharge | Battery voltage: 12 V | Output frequency: 50 Hz | Depth: 350 mm | UPS topology: Line-Interactive | AC outlet types: Type F | Typical backup time at full load: 3 min | Form factor: Tower | Waveform: Sine | Output power capacity: 1500 kVA | RJ-45 ports quantity: 2 | Response time: 2 - 6 ms | Output operation voltage (min): 255 V | Power protection

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

features: Overvoltage protection | Battery recharge time (90%): 6 h | Power protection features:
Over power | Power protection features: Input fuse | Weight: 11.2 kg | Input operation voltage (min):
145 V | Input operation voltage (max): 290 V