



CyberPower OLS3000ERT2UA uninterruptible power supply (UPS) Double- conversion (Online) 2 kVA 1800 W 8 AC outlet(s)

Modelis: OLS3000ERT2UA

Gamintojas: CYBERPOWER

EAN: 4712856273823

Prekės kodas: 573829

1,003.99€

Certification: CE, EAC | UPS topology: Double-conversion (Online) | Emergency Power Off (EPO) connector: Yes | Display type: LCD | Replacement battery cartridge: RBP0157 | Maximum current: 9 A | Output frequency: 50/60 Hz | Output voltage regulation: 1% | Surge protection: Yes | Efficiency (ECO mode): 95% | Output voltage Total Harmonic Distortion (THD): 5% | ECO mode: Yes | Output operation voltage (min): 208 V | Surge energy rating: 363 J | Audible alarm modes: Battery replacement, Low battery alarm, Overload alarm, Fault, Alarm when on battery | Input frequency:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

50/60 Hz | Serial interface type: RS-232 | Battery life (max): 5 year(s) | EMI/RFI noise filtering: Yes | Output power factor: 0.9 | Harmonized System (HS) code: 8504408590 | USB port type: USB Type-B | Control type: Buttons | Power factor: 0.9 | Input power factor: 0.99 | Waveform: Pure sine | Output power capacity: 2 kVA | AC outlet types: C13 coupler | Charging current: 1.5 A | Serial interface: Yes | Built-in fan: Yes | Crest factor: 3:1 | Heat dissipation: 682 BTU/h | Input operation voltage (min): 190 V | Hot-swap battery: Yes | Non-operating altitude: 0 - 1500 m | Output operation voltage (max): 240 V | Emergency Power Off (EPO): Yes | Rack mount kit: Yes | Input operation voltage (max): 300 V | Output frequency regulation: 0.5 Hz | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: EAC | AC outlets quantity: 8 AC outlet(s) | Width: 438 mm | Operating relative humidity (H-H): 5 - 95% | Battery voltage: 48 V | Storage temperature (T-T): -20 - 50 °C | Output power: 1800 W | Cable length: 1.5 m | Package height: 230 mm | Battery capacity: 9 Ah | Manual: Yes | Product colour: Black | Ethernet LAN (RJ-45) ports: 1 | Response time: 0 ms | Serial ports quantity: 1 | Typical backup time at full load: 3.8 min | Battery technology: Sealed Lead Acid (VRLA) | Weight: 19.2 kg | Cooling type: Active | Form factor: Rackmount/Tower | Number of batteries included: 2 pc(s) | Cables included: Input power cable, USB cable | Height: 88 mm | Depth: 430 mm | USB port: Yes | Power plug: Type F | Typical backup time at half load: 13.1 min | Batteries included: Yes | Rack capacity: 2U | Operating temperature (T-T): 0 - 40 °C | Modem (RJ-11) ports: 1 | Power protection features: Overload | Package width: 540 mm | Operating altitude: 0 - 1500 m | Battery recharge time: 4 h | Storage relative humidity (H-H): -20 - 50% | Housing material: Metal | Audible alarm(s): Yes | Number of batteries supported: 3 | RS-232 ports: 1