



CyberPower OLS3000EA-DE uninterruptible power supply (UPS) Double- conversion (Online) 3 kVA 2700 W 7 AC outlet(s)

Modelis: OLS3000EA

Gamintojas: CYBERPOWER

EAN: 4711027790121

Prekės kodas: 573830

583.99€

Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Operating relative humidity (H-H): 20 - 90% | Replacement battery cartridge: BPSE72V40A | Input power factor: 0.98 | AC outlets quantity: 8 AC outlet(s) | Power protection features: Overload | Power protection features: Input fuse | Typical backup time at full load: 4.3 min | Maximum current: 13.04 A |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Response time: 0 ms | Battery recharge time: 4 h | EMI/RFI noise filtering: Yes | Battery technology: Sealed Lead Acid (VRLA) | Width: 169 mm | Power protection features: Short circuit | Audible alarm modes: Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm | Input frequency: 50/60 Hz | Display type: LCD | Typical backup time at half load: 13.1 min | Output voltage Total Harmonic Distortion (THD): 5% | Package width: 295 mm | Charging current: 1.5 A | Output frequency: 50/60 Hz | Audible alarm(s): Yes | Form factor: Tower | Non-operating altitude: 0 - 1500 m | Output operation voltage (max): 240 V | Waveform: Pure sine | Harmonized System (HS) code: 8504408590 | Power protection features: Over current | Number of batteries supported: 3 | Input operation voltage (min): 190 V | Emergency Power Off (EPO) connector: Yes | Number of input phases: 1 | Power plug: C20 coupler | Storage temperature (T-T): -20 - 50 °C | Crest factor: 3:1 | Height: 337 mm | UPS topology: Double-conversion (Online) | Power factor: 0.9 | Weight: 26 kg | Operating altitude: 0 - 1500 m | Input operation voltage (max): 300 V | Depth: 416 mm | AC outlet types: C19 coupler | USB port: Yes | AC outlet types: C13 coupler | Operating temperature (T-T): 0 - 40 °C | Efficiency (ECO mode): 95% | Output power capacity: 3 kVA | Surge protection: Yes | Output operation voltage (min): 208 V | Surge energy rating: 370 J | Package height: 458 mm | AC outlet types: Terminal | Cable length: 1.5 m | Emergency Power Off (EPO): Yes | Product colour: Black | Output power: 2700 W | Housing material: Metal | Storage relative humidity (H-H): 10 - 90%