

CyberPower OLS3000EA uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 2700 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OLS3000EA** · EAN: **4711027790121** · Prekės kodas: **573830**



572,90 €

Kaina su PVM

Be PVM: **473,47 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Surge and Spike Protection
- ✓ Color LCD Panel
- ✓ Serial Connectivity Port
- ✓ PowerPanel Management Software
- ✓ Tower Form Factor
- ✓ ECO Mode
- ✓ Overload Protection



Aprašymas

CyberPower OLS3000EA is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS is designed with color LCD panel for users to monitor power system and configure settings easily. This model is generator compatible and also adopts ECO mode to conserve power. The product can be connected to Emergency Power Off (EPO) switch, which allows users to shut off UPS immediately during emergency. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users.

Techninė specifikacija

Specifications	
Sandėlio grupė	UPS power supplies [+0][-0]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	13.04 A
Surge energy rating	370 J
Response time	0 ms
Number of input phases	1
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.98
Crest factor	3:1
Emergency Power Off (EPO)	Yes
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Input fuse, Over current, Overload, Short circuit
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler, Terminal
Power plug	C20 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes

Emergency Power Off (EPO) connector	Yes
-------------------------------------	-----

Battery

Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	3
Typical backup time at full load	4.3 min
Typical backup time at half load	13.1 min
Battery recharge time	4 h
Charging current	1.5 A
Replacement battery cartridge	BPSE72V40A

Design

Form factor	Tower
Product colour	Black
Housing material	Metal
Cable length	1.5 m
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m

Certificates

Compliance certificates	CE, RoHS
-------------------------	----------

Weight & dimensions

Width	169 mm
Depth	416 mm
Height	337 mm
Weight	26 kg

Packaging data

Package width	295 mm
Package depth	519 mm
Package height	458 mm
Package weight	30.4 kg

Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Matmenys ir svoris	
Matmenys (l × p × A)	51,00cm × 45,00cm × 30,00cm
Svoris	27,50kg