



CyberPower VP1200EILCD uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 8 AC outlet(s)

Modelis: VP1200EILCD

Gamintojas: CYBERPOWER

EAN: 4712856274905

Prekės kodas: 573832

241.00€

AC outlets quantity: 8 AC outlet(s) | Operating temperature (T-T): 0 - 40 °C | Weight: 9.62 kg |
Operating altitude: 0 - 3000 m | Storage temperature (T-T): -20 - 50 °C | USB 2.0 ports quantity: 1 |
Product colour: Black | Ethernet LAN (RJ-45) ports: 1 | Response time: 4 ms | Power protection
features: Overload | Operating relative humidity (H-H): 0 - 90% | Height: 281 mm | Power plug: C14
coupler | Output frequency: 50/60 Hz | Cables included: USB cable | Package height: 384 mm |
Depth: 355 mm | Output power: 720 W | Surge protection: Yes | Audible alarm(s): Yes | USB port: Yes
| Form factor: Tower | Package width: 430 mm | Modem (RJ-11) ports: 1 | Storage relative humidity
(H-H): 0 - 90% | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Compliance

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

certificates: RoHS | Typical backup time at half load: 12 min | Audible alarm modes: Fault, Low battery alarm, Overload alarm | Maximum current: 5.2 A | Input frequency: 50/60 Hz | Typical backup time at full load: 4 min | UPS topology: Line-Interactive | Non-operating altitude: 0 - 3000 m | Output operation voltage (max): 230 V | Cabling technology: 10/100/1000Base-T(X) | Battery recharge time: 8 h | Surge energy rating: 450 J | Waveform: Sine | Harmonized System (HS) code: 8504408590 | Output operation voltage (min): 230 V | Input operation voltage (min): 167 V | AC outlet types: C13 coupler | Output power capacity: 1.2 kVA | EMI/RFI noise filtering: Yes | Automatic Voltage Regulation (AVR): Yes | Input operation voltage (max): 295 V | Display type: LCD