



Gembird EG-UPS-036 uninterruptible power supply (UPS) Line- Interactive 3 kVA 1800 W 6 AC outlet(s)

Modelis: EG-UPS-036

Gamintojas: ENERGENIE

EAN: 8716309124744

Prekės kodas: 573839

255.99€

AC outlets quantity: 6 AC outlet(s) | Battery voltage: 12 V | Response time: 10 ms | USB 2.0 ports quantity: 1 | Operating temperature (T-T): 0 - 40 °C | Weight: 19 kg | Noise level: 45 dB | Package type: Box | Ethernet LAN (RJ-45) ports: 1 | Operating relative humidity (H-H): 20 - 90% | Battery capacity: 7 Ah | Product colour: Black | Form factor: Compact | Sustainability compliance: Yes | Warnings: Keep away from sources of fire and water. | Customs product code (TARIC): 8504408590 | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Compliance certificates: RoHS | Compliance certificates: CE | Output power capacity: 3 kVA | Typical backup time at full load: 20 min | Power protection features: Short circuit | Power protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Overdischarge | Package height: 150 mm | Typical backup time at half load: 8 min | Input frequency: 50/60 Hz | Depth: 400 mm | USB port: Yes | Surge protection: Yes | Package width: 300 mm | Height: 125 mm | Display type: LCD | Width: 220 mm | Cables included: Input power cable, USB cable | Number of batteries supported: 4 | Battery technology: Sealed Lead Acid (VRLA) | Cold start: Yes | Output power: 1800 W | Audible alarm(s): Yes | Power protection features: Overcharge | USB port type: USB Type-B | Power plug: C14 coupler | Charging current: 1.2 A | AC outlet types: Type F | Waveform: Sine | AC outlet types: C13 coupler | Number of type F outputs: 3 | Automatic Voltage Regulation (AVR): Yes | Input operation voltage (max): 295 V | UPS topology: Line-Interactive | Battery recharge time (90%): 8 h | Input operation voltage (min): 162 V | Output operation voltage (max): 220 V