

UPS EVER DUO 350 AVR (TWR; 350VA) (T/DAVRTO-000K35/00)

Gamintojas: **EVER** · Modelis: **T/DAVRTO-000K35/00** · EAN: **5907683605117** · Prekės kodas: **573843**



93,90 €

Kaina su PVM

Be PVM: **77,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Output operation voltage (max): 253 V | Surge protection: Yes | International Protection (IP) code: IP20 | Power protection features: Short circuit | Weight: 3.8 kg | Storage relative humidity (H-H): 20 - 95% | Cold start: Yes | Power protection features: Overload | Battery voltage: 12 V | Package width: 122 mm | AC outlets quantity: 2 AC outlet(s) | Form factor: Tower | Output power capacity: 0.35 kVA | Input operation voltage (min): 162 V | Output operation voltage (min): 191 V | Audible alarm(s): Yes | Input operation voltage (max): 290 V | Battery capacity: 5 Ah | Depth: 286 mm | Operating temperature (T-T): 0 - 40 °C | Input frequency: 50/60 Hz | Package height: 225 mm | Storage temperature (T-T): 0 - 40 °C | Number of batteries supported: 1 | Product colour: Black | Operating relative humidity (H-H): 20 - 80% | Height: 158 mm | Output power: 245 W | Width: 84 mm | Battery technology: Sealed Lead Acid (VRLA) | Automatic Voltage Regulation (AVR): Yes | Waveform: Sine | Audible alarm modes: Fault, Low battery alarm, Overload alarm | Output frequency: 50/60 Hz | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | UPS topology: Line-Interactive | AC outlet types: C13 coupler | Number of output phases: 1 | Number of input phases: 1

Techninė specifikacija

Matmenys ir svoris

Matmenys (I × P × A)	29,00cm × 12,00cm × 23,00cm
Svoris	4,07kg