

UPS EVER DUO 550 AVR USB (TWR; 550VA) (T/DAVRTO-000K55/00)

Gamintojas: **EVER** · Modelis: **T/DAVRTO-000K55/00** · EAN: **5907683605124** · Prekės kodas: **573844**



107,90 €

Kaina su PVM

Be PVM: 89,17 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Output frequency: 50/60 Hz | Automatic Voltage Regulation (AVR): Yes | USB port type: USB Type-B | Waveform: Sine | Power protection features: Overload | Output operation voltage (max): 253 V | Operating relative humidity (H-H): 20 - 80% | Output power: 330 W | Package width: 122 mm | Storage relative humidity (H-H): 20 - 95% | International Protection (IP) code: IP20 | Input operation voltage (max): 290 V | Form factor: Tower | Weight: 3.8 kg | AC outlets quantity: 4 AC outlet(s) | Audible alarm modes: Fault, Low battery alarm, Overload alarm | Input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 40 °C | Width: 84 mm | Power protection features: Short circuit | Product colour: Black | Cold start: Yes | Storage temperature (T-T): 0 - 40 °C | Number of output phases: 1 | Depth: 252 mm | UPS topology: Line-Interactive | Audible alarm(s): Yes | Battery voltage: 12 V | Height: 158 mm | Input operation voltage (min): 162 V | Number of input phases: 1 | Output operation voltage (min): 191 V | Output power capacity: 0.55 kVA | AC outlet types: C13 coupler | Battery capacity: 5 Ah | Battery technology: Sealed Lead Acid (VRLA) | Package height: 225 mm | Number of batteries supported: 1 | USB port: Yes | Surge protection: Yes | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating.

Techninė specifikacija

Specifications

Sandėlio grupė

UPS power supplies [+0][-0]

Matmenys ir svoris

Matmenys (I × P × A)	29,00cm × 13,00cm × 23,00cm
Svoris	4,36kg