



UPS EVER ECO Pro 1200 AVR CDS 19 (Rack; 1200VA) (W/EAVRRM- 001K20/00)

Modelis: W/EAVRRM-001K20/00

Gamintojas: EVER

EAN: 5907683604875

Prekės kodas: 573846

357.99€

UPS topology: Line-Interactive | Output operation voltage (min): 184 V | Cold start: Yes | Number of output phases: 1 | Waveform: Sine | AC outlet types: IEC 320 | Output frequency: 50 Hz | EMI/RFI noise filtering: Yes | Surge protection: Yes | USB port type: USB Type-B | Input operation voltage (min): 168 V | Input operation voltage (max): 264 V | Automatic Voltage Regulation (AVR): Yes | Number of input phases: 1 | Output operation voltage (max): 264 V | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | USB port: Yes | Rack capacity: 2U | Storage temperature (T-T): 0 - 40 °C | Output power capacity: 1.2 kVA | Depth: 200 mm | Output power: 780 W | Input frequency: 50 Hz | Product colour: Black | Operating temperature (T-T): 0 - 40 °C | Storage relative humidity (H-H): 20 - 95% | Form factor: Rackmount |

AC outlets quantity: 3 AC outlet(s) | Number of batteries supported: 2 | Power protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Short circuit | Width: 485 mm | Audible alarm(s): Yes | Power protection features: Overload | Package width: 505 mm | International Protection (IP) code: IP20 | Height: 88 mm | Weight: 11.4 kg | Operating relative humidity (H-H): 20 - 80% | Battery technology: Sealed Lead Acid (VRLA) | Battery voltage: 12 V | Battery capacity: 5 Ah | Package height: 160 mm