



TP-Link Omada AX3000 Ceiling Mount WiFi 6 Access Point



Modelis: EAP650

Gamintojas: TP-LINK

EAN: 4897098683545

Prekės kodas: 574453

120.99€

Certification: CE, FCC, RoHS | 5 GHz: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Frequency band: 2.4 - 5 GHz | Mounting kit: Yes | VLAN support: Yes | LED indicators: Yes | Networking standards: IEEE 802.1x | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Reset button: Yes | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Quick start guide: Yes | Syslog: Yes | Security algorithms: WPA3-Enterprise | Product colour: White | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11ac | Security algorithms: SNMPv3 | MIMO type: Multi User MIMO | Depth: 160 mm | Package type: Box | Networking standards: IEEE 802.11ax | Antenna type: Internal | Security algorithms: WPA2-PSK | Ethernet LAN data rates: 100 Mbit/s | Networking standards: IEEE 802.11a | Rate limiting: Yes | Web-based management: Yes | MAC address filtering: Yes | Placement: Ceiling, Wall | Number of users: 250 user(s) | Spread spectrum method: OFDMA | Airtime Fairness (ATF): Yes | Security algorithms: SSH | Security algorithms: WPA-Enterprise | Height: 33.6 mm | Maximum data transfer rate: 2976 Mbit/s | Flow control support: Yes | Networking standards: IEEE 802.3at | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Automatic channel

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

scanning: Yes | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN data rates: 1000 | Number of products included: 1 pc(s) | Transmitting power (CE): 20 dBm(2.4 GHz, EIRP) 23 dBm(5 GHz, Band1 & Band2, EIRP) 30 dBm(5 GHz, Band3, EIRP) | Automatic channel selection: Yes | DC voltage range: 12 V | DC-in jack: Yes | Operating relative humidity (H-H): 10 - 90% | Fit AP mode features: Mesh networking | Operating temperature (T-T): 0 - 40 °C | 2.4 GHz: Yes | Ethernet LAN (RJ-45) ports: 1 | Maximum data transfer rate (2.4 GHz): 574 Mbit/s | Security algorithms: SNMP | Access Control List (ACL): Yes | Power over Ethernet (PoE): Yes | Maximum data transfer rate (5 GHz): 2402 Mbit/s | BeamForming: Yes | 6 GHz: No | Width: 160 mm | Band steering: Yes | Transmitting power (FCC): 25 dBm (2.4 GHz) 25 dBm (5 GHz)