



MSI MAG A1000GL PCIE5 II power supply unit 1000 W 24- pin ATX ATX Black

Modelis: 306-7ZP9D11-CE0

Gamintojas: MSI

EAN: 4711377246729

Prekės kodas: 574486

153.98€

Cooling type: Active | Width: 150 mm | AC input voltage: 100 - 240 V | AC input frequency: 50/60 Hz |
EPS power connector (8-pin): No | Product colour: Black | Depth: 150 mm | On/off switch: Yes |
Weight: 169 g | Peripheral (Molex) power connectors (4-pin): 1 | PCI Express power connectors (16-
pin): 1 | Illumination: No | Combined power (+12V): 999.6 W | Purpose: PC | PCI Express power
connectors (6+2 pin): 4 | Peripheral (Molex) power cable length: 450 mm | Max output current
(+5Vsb): 3 A | Number of SATA power connectors: 12 | Max output current (+5V): 22 A | 80 PLUS
certification: 80 PLUS Gold | Bearing technology: FDB | Power supply unit (PSU) form factor: ATX |
Max output current (+3.3V): 22 A | SATA power cable length: 500 mm | Cabling type: Fully-Modular |
Combined power (+5Vsb): 15 W | Motherboard power cable length: 60 cm | EPS power connector
(4+4 pin): Yes | SATA power cable length: 150 mm | Fan speed: 500 - 1800 RPM | Peripheral (Molex)
power cable length: 500 mm | Combined power (+5V): 120 W | Total power: 1000 W | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

protection features: Overheating | Power protection features: Short circuit | Power protection features: Over voltage | Efficiency: 90% | Power protection features: Over power | Combined power (-12V): 3.6 W | ATX version: 3.1 | Number of +12V rail(s): 1 | Fan diameter: 13.5 cm | Height: 86 mm | Power protection features: Under voltage | Power protection features: Over current | Motherboard power connector: 24-pin ATX | Max output current (-12V): 0.3 A | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 120 W | Max output current (+12V): 83.3 A | Number of fans: 1 fan(s)