



Access Point TP-LINK 3600 Mbps EAP723



Modelis: EAP723

Gamintojas: TP-LINK

EAN: 8885020623031

Prekės kodas: 575283

124.99€

BE5000 Compact Business WiFi 7 Access Point

Optimized Wired Performance with 2.5G PoE+ Port

With a 2.5 GbE Port, EAP723 delivers remarkable multi-gigabit performance for higher bandwidth and faster WiFi. Compatibility with 802.3at PoE is ideal for flexible deployment.

Boosted Network Security

- Secure Guest Network with up to 16 SSIDs
- Boost Your Business with SMS Login
- WPA3 for Worry-Free Open Public Networks
- Rogue AP Detection

- BE5000 Dual-Band Wi-Fi 7 (2882 Mbps on 5 GHz + 688 Mbps on 2.4 GHz)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjanč rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 1× 2.5G port unlocks the full potential of Wi-Fi 7
- 240 MHz bandwidth enables many more simultaneous transmissions
- Multi-RUs ensure the high performance of your network
- Advanced Functions: Centralized management, Mesh, and Seamless Roaming

Summary: TP-Link Omada BE3600 Ceiling Mount Wi-Fi 7 Access Point. 2.4 GHz, 5 GHz, Maximum data transfer rate: 3600 Mbit/s. Security algorithms: SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal,.... Power over Ethernet (PoE). Product colour: White. Power consumption (max): 18.6 W | Vendor Homepage: <https://www.omadanetworks.com/my/business-networking/omada-wifi-ceiling-mount/eap723/> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Airtime Fairness (ATF): Yes | Automatic channel selection: Yes | Band steering: Yes | Bandwidth: 2.4 | BeamForming: Yes | Fit AP mode features: Mesh networking | Frequency band: 2.4 - 5 | Maximum data transfer rate: 3600 | Maximum data transfer rate (2.4 GHz): 688 | Maximum data transfer rate (5 GHz): 2882 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11be/IEEE 802.11g/IEEE 802.11n | Quality of Service (QoS) support: Yes | Rate limiting: Yes | Spread spectrum method: OFDMA | VLAN support: Yes | Access Control List (ACL): Yes | MAC address filtering: Yes | Security algorithms: SNMP/SNMPv2/SNMPv3/WPA2-Enterprise/WPA2-Personal/WPA3-Enterprise/WPA3-Personal/WPA-Enterprise/WPA-Personal | Syslog: Yes | Web-based management: Yes | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | DC voltage range: 12 | Input current: 1.5 | Power consumption (max): 18.6 | Power over Ethernet (PoE): Yes | LED indicators: Yes | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | Antenna gain level (max): 5 | Antenna type: Internal | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC)/RoHS | Depth: 160 | Height: 36.7 | Width: 160 | Package type: Box | Mounting kit: Yes | Quantity per pack: 1 | Quick start guide: Yes | Model: EAP723 | Model name: BE3600 Ceiling Mount Wi-Fi 7 Access Point | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005353 | Unit Calculated Weight: 0.781