HIKVISION DS-2CD1061G2-LIU 2.8mm IP CAMERA ver. PL

Gamintojas: **HIKVISION** · Modelis: **DS-2CD1061G2-LIU 2.8mm PL** · EAN: **6936422131029** · Prekės kodas: **576360**



75,90 €

Kaina su PVM

Be PVM: **62,73 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt





Aprašymas

Audit log: Yes | Number of Privacy masking areas: 4 | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Minimum illumination: 0 lx | Height: 69.1 mm | Operating temperature (T-T): -30 - 60 °C | Package weight: 481 g | Power consumption (max): 5 W | Length: 170.8 mm | Number of cameras: 1 | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 3200 x 1800 | Pan range: 0 - 360° | International Protection (IP) code: IP67 | Wide Dynamic Range (WDR): Yes | Weight: 285 g | Built-in light: Yes | Package height: 118 mm | Ethernet interface type: Fast Ethernet | Connectivity technology: Wired | Signal-to-Noise Ratio (SNR): 52 dB | Product colour: White | Operating relative humidity (H-H): 0 - 95% | Package depth: 121 mm | Storage temperature (T-T): -30 - 60 °C | Width: 66 mm | Highlight Compensation (HLC): Yes | Protection features: Waterproof | Wi-Fi: No | Maximum resolution: 3200 x 1800 pixels | Audio formats supported: G.726 | Supported graphics resolutions: 640 x 360 | Package width: 216 mm | Form factor: Bullet | Bit rate: 32 Kbps - 16 Mbps | Progressive scan: Yes | Bluetooth: No | Housing material: Metal | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Housing material: Plastic | Audio formats supported: G.722.1 | Camera shutter speed: 1 - 1/100000 s | Built-in microphone: Yes | Power source type: DC, PoE | Audio formats supported: G.711 | Web-based management: Yes | Total megapixels: 6 MP | Storage relative humidity (H-H): 0 - 95% | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP | Audio formats supported: MP2L2 | Night vision distance: 30 m | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Audio formats supported: AAC-LC | Type: IP security camera | Client interoperability: iVMS-4200, Hik-Connect | Tilt angle range: 0 - 90° | Digest authentication: Yes | Video motion detection: Yes | Privacy masking: Yes | Number of users: 32 user(s) | Fixed focus: Yes | Built-in HDD: No | Recognize distance: 15 m | Fixed focal length: 2.8 mm | Heartbeat: Yes | Sensor type: CMOS | Digital watermark: Yes | Video streaming: Yes | Password protection: Yes | Infrared (IR) cut-off filter: Yes | Mirror: Yes | Number of languages: 1 | Image quality adjustment: Sharpness | Image quality adjustment: Contrast | Image quality adjustment: White balance | Image quality adjustment: Brightness | DC output current: 0.41 A | Video compression formats: H.265+ | Image quality adjustment: Saturation | Number of lenses: 1 | Maximum aperture number: 1.6 | Video compression formats: H.264 | Languages support: Polish | Number of sensors: 1 | Video compression formats: M-JPEG | Region of Interest (ROI)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

encoding: Yes | Live view: Yes | Day/night mode: Yes | Video compression formats: H.265 | Video compression formats: H.264+ | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Mounting type: Ceiling/wall | DC output voltage: 12 | Power consumption (Power over Ethernet (PoE)): 6.5 W | Privacy protection: Yes | Observe distance: 30 m | Identify distance: 7 m | Infra-red wavelength: 850 nm | Dynamic range: 120 dB | Password reset via email: Yes | Placement supported: Indoor & outdoor | Lens viewing angle, vertical: 55° | Detect distance: 76 m | Number of simultaneous live view channels: 6 channels | User access level: Administrator, Operator, User | Night vision: Yes | Bit rate range: 16 - 160 Kbit/s | Lens viewing angle, horizontal: 105° | Sustainability compliance: Yes | Lens viewing angle, diagonal: 127° | Sample rates: 8 - 16 kHz | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: REACH | Compliance certificates: CB

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	12,00cm × 12,00cm × 22,00cm
Svoris	0,43kg