



HIKVISION DS-2CD1061G2-LIU 2.8mm IP CAMERA



Modelis: DS-2CD1061G2-LIU 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422131029

Prekės kodas: 576360

75.00€

Audit log: Yes | Number of Privacy masking areas: 4 | Package depth: 121 mm | Bluetooth: No | Form factor: Bullet | Product colour: White | Operating temperature (T-T): -30 - 60 °C | Package weight: 481 g | Storage temperature (T-T): -30 - 60 °C | Built-in light: Yes | Ethernet LAN (RJ-45) ports: 1 | Operating relative humidity (H-H): 0 - 95% | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 640 x 360 | Package width: 216 mm | Power consumption (max): 5 W | Length: 170.8 mm | Supported graphics resolutions: 640 x 480 (VGA) | Connectivity technology: Wired | Supported graphics resolutions: 1280 x 720 (HD 720) | Power source type: DC, PoE | Storage relative humidity (H-H): 0 - 95% | Package height: 118 mm | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Tilt angle range: 0 - 90° | Fixed focus: Yes | Signal-to-Noise Ratio (SNR): 52 dB | Audio formats supported: AAC-LC | Audio formats supported: G.726 | Supported graphics resolutions: 3200 x 1800 | Built-in microphone: Yes | Maximum resolution: 3200 x 1800 pixels | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP | Audio formats supported: MP2L2 | Minimum illumination: 0 lx | Number of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

cameras: 1 | Bit rate: 32 Kbps - 16 Mbps | Digest authentication: Yes | Type: IP security camera | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Web-based management: Yes | Audio formats supported: G.722.1 | Night vision distance: 30 m | Progressive scan: Yes | Camera shutter speed: 1 - 1/100000 s | Pan range: 0 - 360° | Weight: 285 g | Number of languages: 1 | Audio formats supported: G.711 | Total megapixels: 6 MP | Bit rate range: 16 - 160 Kbit/s | Protection features: Waterproof | Highlight Compensation (HLC): Yes | International Protection (IP) code: IP67 | Wide Dynamic Range (WDR): Yes | Privacy protection: Yes | Height: 69.1 mm | Wi-Fi: No | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Back Light Compensation (BLC): Yes | Sample rates: 8 - 16 kHz | Client interoperability: iVMS-4200, Hik-Connect | Housing material: Metal | Housing material: Plastic | Width: 66 mm | Built-in HDD: No | Recognize distance: 15 m | DC output voltage: 12 | DC output current: 0.41 A | Day/night mode: Yes | Video compression formats: H.264 | Fixed focal length: 2.8 mm | Digital watermark: Yes | Region of Interest (ROI) encoding: Yes | Languages support: Polish | Number of sensors: 1 | Image quality adjustment: Sharpness | Power consumption (Power over Ethernet (PoE)): 6.5 W | Image quality adjustment: White balance | Number of lenses: 1 | Number of users: 32 user(s) | Heartbeat: Yes | Video compression formats: H.264+ | Image quality adjustment: Saturation | Mirror: Yes | Image quality adjustment: Contrast | Live view: Yes | Mounting type: Ceiling/wall | Video compression formats: H.265+ | Maximum aperture number: 1.6 | Video compression formats: M-JPEG | Observe distance: 30 m | Infra-red wavelength: 850 nm | Image quality adjustment: Brightness | Video compression formats: H.265 | Video motion detection: Yes | Privacy masking: Yes | Infrared (IR) cut-off filter: Yes | Placement supported: Indoor & outdoor | Compliance certificates: Low Voltage Directive (LVD) | Detect distance: 76 m | Video streaming: Yes | Night vision: Yes | Compliance certificates: CB | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: WEEE | Compliance certificates: RCM | Sensor type: CMOS | Compliance certificates: REACH | Dynamic range: 120 dB | Lens viewing angle, horizontal: 105° | Password protection: Yes | Identify distance: 7 m | Lens viewing angle, diagonal: 127° | Password reset via email: Yes | Number of simultaneous live view channels: 6 channels | User access level: Administrator, Operator, User | Sustainability compliance: Yes | Lens viewing angle, vertical: 55°