



**TP-Link Omada
ES208GP
network switch
Managed L2
Gigabit Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
DIN rail Black**

Modelis: ES208GP

Gamintojas: TP-LINK

EAN: 1210002609708

Prekės kodas: 576362

70.99€

Ethernet LAN data rates: 10,100,1000 Mbit/s | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 64 W | Virtual LAN features: Tagged VLAN | Multicast support: Yes | Forwarding rate: 11.904 Mpps | Quick start guide: Yes | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | Power over Ethernet plus (PoE+) ports quantity: 8 | Virtual LAN features: MTU VLAN | DHCP features: DHCP client | Switch layer: L2 | Operating relative humidity (H-H): 10 - 90% | Rack mounting: Yes | Store-and-

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

forward: Yes | Width: 158 mm | Product colour: Black | Input current: 1.31 A | Jumbo frames support: Yes | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | IGMP snooping: Yes | Number of VLANs: 4000 | Power source: DC | Switching capacity: 16 Gbit/s | Flow control support: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 0.5 MB | LED indicators: Yes | Loop protection: Yes | Form factor: DIN rail | Link aggregation: Yes | Broadcast storm control: Yes | 10G support: No | Port mirroring: Yes | Switch type: Managed | Height: 25.4 mm | Cables included: Power | Web-based management: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3at | Auto MDI/MDI-X: Yes | Networking standards: IEEE 802.3bt | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3af | Transmission distance (max): 0.25 km | Power over Ethernet (PoE) type supported: PoE+ | DC input voltage: 53 V | Compliance certificates: Federal Communications Commission (FCC) | Jumbo frames: 15000 | Compliance certificates: RoHS | Compliance certificates: CE | Cloud-managed: Yes