



CyberPower BR1000ELCD-FR uninterruptible power supply (UPS) Line- Interactive 1 kVA 600 W 8 AC outlet(s)

Modelis: BR1000ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856271249

Prekės kodas: 576379

172.99€

Certification: CE | Output power capacity: 1 kVA | AC outlet types: Type E | Depth: 288 mm |
Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away
from sources of fire and water. | Housing material: Plastic | EMI/RFI noise filtering: Yes | USB port: Yes
| UPS topology: Line-Interactive | Output frequency: 50/60 Hz | Typical backup time at half load: 6
min | Modem (RJ-11) ports: 2 | Surge protection: Yes | Cold start: Yes | Automatic Voltage Regulation
(AVR): Yes | Width: 166 mm | Surge energy rating: 125 J | Power protection features: Overload |
Waveform: Sine | Surge protection features: Fax | Surge protection features: Modem | Surge
protection features: Digital Subscriber Line (DSL) | Surge protection features: Network | Surge

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

protection features: Telephone | Audible alarm(s): Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Input operation voltage (max): 290 V | Typical backup time at full load: 1 min | Input operation voltage (min): 165 V | Input frequency: 50/60 Hz | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Battery technology: Sealed Lead Acid (VRLA) | Output power: 600 W | Display type: LCD | Height: 118 mm | Non-operating altitude: 0 - 3000 m | Battery recharge time: 8 h | Compliance certificates: RoHS | Response time: 4 ms | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 2 | AC outlets quantity: 8 AC outlet(s) | Operating relative humidity (H-H): 0 - 90% | Product colour: Black | Storage temperature (T-T): -20 - 50 °C | Weight: 6.5 kg | Storage relative humidity (H-H): 0 - 90% | Cable length: 1.5 m | Form factor: Compact | Operating altitude: 0 - 3000 m | USB 2.0 ports quantity: 1 | LED indicators: Yes