



CyberPower UT1050EG-FR uninterruptible power supply (UPS) Line- Interactive 1.05 kVA 630 W 4 AC outlet(s)

Modelis: UT1050EG-FR

Gamintojas: CYBERPOWER

EAN: 4712856273526

Prekės kodas: 576380

156.99€

Certification: CE, EAC | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Compliance certificates: RoHS | Input frequency: 50/60 Hz | Form factor: Tower | Waveform: Sine | Surge protection features: Modem | Storage temperature (T-T): -20 - 50 °C | Output power: 630 W | UPS topology: Line-Interactive | EMI/RFI noise filtering: Yes | Output power capacity: 1.05 kVA | AC outlet types: Type E | AC outlets quantity: 4 AC outlet(s) | Power protection features: Overload | Surge protection features: Fax | USB port: Yes |

Cabling technology: 10/100/1000Base-T(X) | Operating temperature (T-T): 0 - 40 °C | Automatic

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Voltage Regulation (AVR): Yes | Output frequency: 50/60 Hz | Surge protection features: Network | Width: 95 mm | Power protection features: Short circuit | Audible alarm(s): Yes | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Depth: 307 mm | Storage relative humidity (H-H): 0 - 90% | Surge protection features: Digital Subscriber Line (DSL) | Response time: 4 ms | Housing material: Plastic | Weight: 6.9 kg | Product colour: Black | Ethernet LAN (RJ-45) ports: 2 | Operating relative humidity (H-H): 0 - 90% | Surge energy rating: 150 J | Battery technology: Sealed Lead Acid (VRLA) | Height: 220 mm | Battery recharge time: 6 h | Input operation voltage (min): 165 V | Number of input phases: 1 | Non-operating altitude: 0 - 3000 m | Output operation voltage (max): 230 V | Input operation voltage (max): 290 V | LED indicators: Yes | Operating altitude: 0 - 3000 m