

# Dahua Technology PFS3211-8GT-120-V2 tinklo komutatorius Ne-valdomas Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Stalinis / tvirtinamas prie sienos Juoda

Gamintojas: **DAHUA** · Modelis: **PFS3211-8GT-120-V2** · EAN: **6923172525482** · Prekės kodas: **576462**



## 168,90 €

Kaina su PVM

Be PVM: **139,59 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Ne-valdomas
- ✓ Pagrindinių perjungimo RJ-45 etherneto prievadų skaičius: 9
- ✓ Cat5e, Cat6
- ✓ Perjungimo pajėgumas: 33 Gbit/s
- ✓ Stalinis / tvirtinamas prie sienos
- ✓ DC Maitinimas per Eternetą (PoE)



## Aprašymas

DH-PFS3211-8GT-120 is an unmanaged Hardened PoE Switch with 8 × 10/100/1000 Mbps PoE Ports. It provides 8 × 10/100/1000 Mbps Ethernet ports , 2 × 1000 Mbps uplink SFPs and 1 × 10/100/1000 Mbps Ethernet uplink ports . The product is equipped with two types of transmission modes (Extend Mode On/Extend Mode Off). The red port supports the IEEE802.3bt and the Hi-PoE standards. The maximum power consumption is 120W. It also supports PoE watchdog to avoid manually maintenance and device restart, which can realize the intelligent management and reduce the cost.

## Intelligent PoE

Provides control over power consumption and offers real-time monitoring to ensure power supplies receive priority with important ports and to prevent malfunctions caused by changes in power consumption. Supports ultra wide power supplies and is able to adapt to IPC power fluctuations.

## BT 90W

The red ports support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards, with a maximum output power consumption rate of 90W per port. Suitable for powering high-power devices.

## PoE Watchdog

Adopts the innovative PoE Watchdog. PoE Watchdog can be switched on by dialing or turning on the WEB page switch. It enables the switch to automatically detect port status and restart failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its truest sense, effectively reducing manual maintenance costs.

## Long Distance PoE

By dialing or enabling long-range transmission on the WEB interface, the transmission distance of a PoE port can be up to 250 m, meeting the requirements of wired transmission (bandwidth reduced to 10 Mbps).

## 8-pin Assignment PoE Power Supply

Supports 8-pin simultaneous power supply (1/2/4/5 positive, 3/6/7/8 negative). Signal lines and idle lines supply power at the same time. Compatibility with IPC is enhanced. Cable loss is reduced. Loading capacity is increased.

The device is applicable for use in different scenarios, including home, office, server farm, and small mall.

## Techninė specifikacija

| Valdymo funkcijos                                       |                                                                                                            |
|---------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Perjungimo tipas                                        | Ne-valdomas                                                                                                |
| Ryšys                                                   |                                                                                                            |
| Pagrindinių perjungimo RJ-45 ethernet prievadų skaičius | 9                                                                                                          |
| Pagrindinių perjungimo RJ-45 ethernet prievadų tipas    | Gigabit Ethernet (10/100/1000)                                                                             |
| Įdiegtų SFP modulių kiekis                              | 2                                                                                                          |
| Gigabit Ethernet (varinis) portų kiekis                 | 9                                                                                                          |
| Tinklas                                                 |                                                                                                            |
| Tinklo standartai                                       | IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x |
| 10G parama                                              | Ne                                                                                                         |
| Palaikomi laidų tipai                                   | Cat5e, Cat6                                                                                                |
| Srauto kontrolės palaikymas                             | Taip                                                                                                       |
| Ethernet LAN duomenų perdavimo norma                    | 10,100,1000 Mbit/s                                                                                         |
| Šviesolaidis                                            |                                                                                                            |

|                                                     |                                    |
|-----------------------------------------------------|------------------------------------|
| Optinių perjungimo blokų tipas                      | Gigabitinis eternetas              |
| <b>Duomenų perdavimas</b>                           |                                    |
| Perjungimo pajėgumas                                | 33 Gbit/s                          |
| Persiuntimo dažnis                                  | 16,37 Mpps                         |
| Paketo buferio atmintis                             | 1,75 MB                            |
| <b>Konstrukcija</b>                                 |                                    |
| Stovo montavimas                                    | Ne                                 |
| Didinimas                                           | Ne                                 |
| Forma                                               | Stalinis / tvirtinamas prie sienos |
| Produkto spalva                                     | Juoda                              |
| LED indikatoriai                                    | Taip                               |
| Montuojamas ant sienos                              | Taip                               |
| <b>Energijos valdymas</b>                           |                                    |
| Maitinimo šaltinis                                  | DC                                 |
| DC įėjimo įtampa                                    | 48 - 57 V                          |
| Galios suvartojimas (maks.)                         | 120 W                              |
| Atsižvelkite į energijos suvartojimą                | Idling: 5 W                        |
| Energijos valdymas                                  | Taip                               |
| Maitinimo apsaugos ypatybės                         | Perkrova                           |
| <b>„Power over Ethernet“ (PoE)</b>                  |                                    |
| Maitinimas per Eternetą (PoE)                       | Taip                               |
| Maitinimo per Eternetą (PoE) prievadų skaičius      | 8                                  |
| Maitinimo per Eternetą (PoE) galia prievadui        | 90 W                               |
| Bendrosios galios per Eternetą (PoE) charakteriskos | 120 W                              |
| <b>Aplinkos sąlygos</b>                             |                                    |
| Darbo temperatūros diapazonas (TT)                  | -30 - 65 °C                        |
| Darbo santykinės drėgmės diapazonas                 | 5 - 95%                            |
| <b>Svoris ir matmenys</b>                           |                                    |
| Plotis                                              | 150 mm                             |
| Ilgis                                               | 100 mm                             |
| Aukštis                                             | 42 mm                              |
| Svoris                                              | 670 g                              |
| <b>Matmenys ir svoris</b>                           |                                    |
| Matmenys (I × P × A)                                | 24,00cm × 8,00cm × 27,00cm         |

Svoris

1,50kg

## Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

## Gamintojo ir saugos informacija

### GAMINTOJAS

**Zhejiang Dahua Technology Co., Ltd**

Bin'an Road, Binjiang District No.1187 & 1199,  
310053 Hangzhou, CN  
[dahuasecurity.com](http://dahuasecurity.com)

### ATSAKINGAS ASMUO ES

**Dahua Technology GmbH**

Niederkasseler Lohweg 185, 40547 Düsseldorf,  
DE  
[dahuasecurity.com](http://dahuasecurity.com)

### PLATINTOJAS

**MB KOMPIUTERIŲ GURU**

V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](mailto:info@shopro.lt)