

Philips E Line 346E2CUAE/00 computer monitor 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD+ LCD Black

Gamintojas: **PHILIPS** · Modelis: **346E2CUAE/00** · EAN: **8712581770662** · Prekės kodas: **57672**



297,90 € ~~315,89 €~~

Kaina su PVM

Be PVM: **246,20 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 86.4 cm (34") Black
- ✓ Height adjustment 10 cm Built-in speaker(s)
- ✓ USB upstream port type: USB Type-C HDMI HDMI version: 2.0
DisplayPorts quantity: 1 DisplayPort version: 1.2
- ✓ Screen shape: Curved
- ✓ Maximum refresh rate: 100 Hz Response time: 4 ms Response time (MPRT): 1 ms
- ✓ 3440 x 1440 pixels Wide Quad HD+ Panel type: VA
- ✓ Energy efficiency class (SDR): F RoHS



Aprašymas

The Philips E line curved UltraWide display offers expansive panoramic visuals. A WQHD display with an ergonomic stand make for optimal viewing conditions. All-in-one USB-C and MultiView meet the need for productivity.

Techninė specifikacija

Specifications

Sandėlio grupė

Monitors, displays, projectors > Monitors [+2][-0]

Display	
Display diagonal	86.4 cm (34")
Display resolution	3440 x 1440 pixels
Native aspect ratio	21:9
Display technology	LCD
Touchscreen	No
HD type	Wide Quad HD+
Panel type	VA
Response time	4 ms
Screen shape	Curved
Contrast ratio (typical)	3000:1
Maximum refresh rate	100 Hz
Display number of colours	1.07 billion colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (peak)	350 cd/m²
Display brightness (typical)	300 cd/m²
Response time (MPRT)	1 ms
Display surface	Matt
Anti-glare screen	Yes
Screen curvature rating	1500R
Aspect ratio	21:9
Dynamic contrast ratio marketing name	Mega Infinity DCR
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Response time (fast)	1 ms
Pixel pitch	0.23175 x 0.23175 mm
Pixel density	110 ppi
Horizontal scan range	30 - 160 kHz
Vertical scan range	48 - 100 Hz
Viewable size, horizontal	79.7 cm
Viewable size, vertical	33.4 cm
Digital horizontal frequency	30 - 160 kHz
Digital vertical frequency	48 - 120 Hz
Display diagonal (metric)	86.36 cm

DDC/CI	Yes
Haze rate	25%
Surface hardness	3H
Colour gamut standard	sRGB, NTSC
Colour gamut	99.5%
sRGB coverage (typical)	121.3%
NTSC coverage (typical)	99.5%
Display sRGB	Yes
Display panel size	34 inch/86.36 cm
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	Yes
AMD FreeSync type	FreeSync Premium
Component video sync	Separate Sync
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	10 W
Design	
Product colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	No
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of USB Type-B upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes

USB Power Delivery up to	65 W
VGA (D-Sub) ports quantity	0
DVI port	No
HDMI ports quantity	1
HDMI version	2
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	No
Audio output	Yes
DC-in jack	Yes
I/O ports	USB-C x 1, USB 3.2 x 4 (downstream with 1 fast charge B. C 1.2)
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Adjustable height (max)	10 cm
Tilt adjustment	Yes
Tilt angle range	-5 - 20°
Picture-in-Picture	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	Yes
LED indicators	Operation, Stand-by
Power	
Energy efficiency class (SDR)	F
Energy consumption (SDR) per 1000 hours	31 kWh
Power consumption (typical)	49.7 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V

AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (with stand)	807 mm
Depth (with stand)	257 mm
Height (with stand)	495 mm
Weight (with stand)	10.1 kg
Width (without stand)	807 mm
Depth (without stand)	110 mm
Height (without stand)	367 mm
Weight (without stand)	7.83 kg
Packaging data	
Package width	980 mm
Package depth	224 mm
Package height	500 mm
Package weight	13.1 kg
Packaging content	
Stand included	Yes
Cables included	USB Type-C to USB Type-C, AC
Manual	Yes
Sustainability	
Doesn't contain	Mercury, PVC/BFR
Other features	
Compatible operating systems	Mac OS X; Windows 10/8.1/8/7
USB Power Delivery revision	3
Picture-by-Picture (PbP)	Yes
Exterior finish type	Textured

Monitor sync input signal	Separate Sync
Heavy metals free	Hg (mercury), Pb (lead)
EasyRead mode	Yes
LowBlue mode	Yes
Compliance certificates	RoHS
Mean time between failures (MTBF)	50000 h
Certification	cETLus, CB, TUV/GS, TUV Ergo, CU-EAC, EAEU RoHS, CE Mark, FCC Class B, ICES-003, UKRAINIAN
User controls	Power On/Off; Menu; Volume; Input; SmartImage
Picture enhancement	SmartImage
MultiView	PIP/PBP mode; 2 x devices
Regulatory Approvals	cETLus; CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; UKRAINIAN; CEC; EAC; MEPS; PSB; UKCA; EMF
Recycling data	
Packaging recyclability rate	100%
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	98,00cm × 22,00cm × 50,00cm
Svoris	12,80kg