



Akyga AK-B1-550 power supply unit 550 W 20+4 pin ATX ATX Grey

Modelis: AK-B1-550

Gamintojas: AKYGA

EAN: 5901720130341

Prekės kodas: 577040

32.98€

Certification: CE, REACH | Depth: 140 mm | Efficiency: 70% | Input current: 5 A | Max output current (+5V): 36 A | AC input voltage: 230 V | Package depth: 220 mm | Package weight: 1.12 kg | Manual: Yes | PCI Express power connectors (6-pin): 1 | Max output current (-12V): 0.5 A | Max output current (+12V): 24 A | Height: 85 mm | Combined power (-12V): 18.5 W | Peak power: 550 W | Warranty card: Yes | Cabling type: Non-Modular | Combined power (+3.3V): 280 W | Power protection features: Over power | Max output current (+5Vsb): 2.5 A | Package width: 160 mm | Product colour: Grey | Power supply unit (PSU) form factor: ATX | Power protection features: Overheating | Number of SATA power connectors: 3 | SATA power cable length: 300 mm | Total power: 550 W | Weight: 1.04 kg | Cooling type: Active | Fan location: Top | Power protection features: Over current | Power protection features: Short circuit | Power protection features: Over voltage | Combined power (+5Vsb): 18.5 W | Peripheral (Molex) power connectors (4-pin): 2 | Operating temperature (T-T): 5 - 50 °C | Sustainability certificates: RoHS | CPU P4 connector (4-pin): 1 | Mean time between failures (MTBF):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

100000 h | On/off switch: Yes | Purpose: PC | Supported motherboard form factors: ATX | CPU power cable length: 45 cm | ATX version: 2.31 | Motherboard power connector: 20+4 pin ATX | Combined power (+12V): 288 W | Fan diameter: 12 cm | Package height: 95 mm | Peripheral (Molex) power cable length: 300 | Package type: Box | Number of fans: 1 fan(s) | Width: 150 mm | Combined power (+5V): 280 W | Max output current (+3.3V): 33 A