



Akyga AK-B1-700 power supply unit 700 W 20+4 pin ATX ATX Grey



Modelis: AK-B1-700

Gamintojas: AKYGA

EAN: 5901720131485

Prekės kodas: 577041

45.99€

Certification: CE, FCC, RoHS, REACH | Operating temperature (T-T): 5 - 50 °C | Motherboard power connector: 20+4 pin ATX | Fan diameter: 12 cm | ATX version: 2.31 | Combined power (-12V): 18.5 W | AC input frequency: 50 Hz | On/off switch: Yes | Product colour: Grey | Package depth: 260 mm | Power supply unit (PSU) form factor: ATX | Package width: 180 mm | SATA power cable length: 300 mm | Mean time between failures (MTBF): 100000 h | SATA power cable length: 150 mm | Total power: 700 W | Number of fans: 1 fan(s) | Height: 85 mm | Max output current (-12V): 0.5 A | AC input voltage: 220 - 230 V | EPS power connector (4+4 pin): Yes | Power protection features: Over current | Combined power (+3.3V): 300 W | Power protection features: Overheating | Power protection features: Short circuit | Power protection features: Over voltage | Combined power (+5Vsb): 18.5 W | Depth: 160 mm | Efficiency: 70% | EPS cable length: 60 cm | Max output current (+5V): 38 A | Weight: 1.26 kg | Cooling type: Active | Package weight: 1.33 kg | Power Factor Correction (PFC) type: Passive | PCI Express power cable length: 45 cm | Max output current (+3.3V):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

35 A | Power protection features: Over power | PCI Express power connectors (6+2 pin): 2 | Max output current (+5Vsb): 2.5 A | Purpose: PC | Peripheral (Molex) power connectors (4-pin): 2 | Package height: 95 mm | Peripheral (Molex) power cable length: 300 | Package type: Box | Motherboard power cable length: 45 cm | Peripheral (Molex) power cable length: 150 mm | Fan location: Side | Cabling type: Non-Modular | Width: 150 mm | Max output current (+12V): 32 A | Number of SATA power connectors: 5 | Combined power (+5V): 300 W | Combined power (+12V): 384 W | Compliance certificates: RoHS