

D-Link DMC-G01LC/E network media converter 1000 Mbit/s Grey

Gamintojas: **D-LINK** · Modelis: **DMC-G01LC/E** · EAN: **790069415982** · Prekės kodas: **577369**



48,90 €

Kaina su PVM

Be PVM: **40,41 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 1000 Mbit/s
- ✓ Ethernet LAN (RJ-45) ports: 1 DC-in jack
- ✓ Fiber ports quantity: 1 SFP
- ✓ Grey



Aprašymas

D-Link's DMC-G01LC standalone media Converter turns a copper Ethernet link into a fiber link, allowing for an ultra-fast, long distance connection. Installation of a standalone media converter is simple, and allows you to tap into fiber speeds with ease. Instead of requiring an investment in an entire chassis, a standalone media converter provides the same high-quality conversion on a unit-by-unit basis. You can save space and cut costs while still extending your network over long distances of 10 km and beyond on a fiber optic line.

SFP Optical Transceivers for Maximum Flexibility

The fiber side of the DMC-G01LC utilizes a 100/1000 SFP port for maximum flexibility. Using the appropriate SFP transceiver (purchased separately) it can support either multimode or single-mode fiber, varying wavelengths, and speeds of either 100 Mbps or 1000 Mbps.

10/100/1000 Copper Speeds

The copper side of the DMC-G01LC auto-negotiates to 10Mbps, 100Mbps or 1000Mbps, ensuring the connection functions at the highest possible speed while remaining compatible with the link partner. It supports auto MDI/MDIX, half/full duplex operation at 10/100 Mbps and full duplex operation at 1000 Mbps.

Plug & Play

The DMC-G01LC supports standard technologies that makes it easy to operate, like 802.3u, 802.3x and 802.3ab. There's no management software to configure – simply connect the power, connect the cables, and start converting.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto MDI/MDI-X	Yes
Performance	
Mean time between failures (MTBF)	506711 h
Features	
Internal	No
LED indicators	Yes
Product colour	Grey
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes
Power	
Input voltage	230 - 240 V
Output voltage	5 V
Output current	1 A
Weight & dimensions	
Width	70 mm
Depth	95 mm
Height	25 mm

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Packaging data

Package width	101 mm
Package depth	134 mm
Package height	95 mm
Package weight	358 g

Certificates

Safety	LVD, UL/cUL
Certification	CE, FCC, VCCI, BSMI

Logistics data

Shipping (inner) case length	50.4 cm
Shipping (inner) case width	29.4 cm
Shipping (inner) case height	23.6 cm
Shipping (inner) case net weight	7.16 kg
Products per shipping (inner) case	20 pc(s)
Pallet gross weight (air)	341.1 kg
Master (outer) cases per pallet (air)	40 pc(s)
Products per pallet (air)	800 pc(s)
Pallet gross length	110 cm
Pallet gross width	120 cm
Pallet height (air)	131 cm
Pallet gross weight (sea)	534.6 kg
Master (outer) cases per pallet (sea)	64 pc(s)
Products per pallet (sea)	1280 pc(s)
Pallet height (sea)	2.02 m
Shipping (inner) case gross weight	8.04 kg
Harmonized System (HS) code	85176990