

FSP Champ Rack 2K nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 2 kVA 1800 W 3 AC išvestis(ys / čių)

Gamintojas: **FSP GROUP** · Modelis: **PPF18A1401** · EAN: **4713224520617** · Prekės kodas: **577416**



621,90 €

Kaina su PVM

Be PVM: **513,97 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 2 kVA 1800 W
- ✓ Signalų forma: Gryna sinusoidė
- ✓ 3 AC išvestis(ys / čių)
- ✓ 12 V 9 Ah
- ✓ Stelažas Juoda



Aprašymas

FSP Champ Rack Series is the high density version of double-conversion online UPS with a output power factor 0.9. It's designed in small cabinet with microprocessor controller. It also has USB and RS-232 communication ports as standard, with a built-in intelligent slot for additional adapters, protocol converters and relate contact cards.

Techninė specifikacija

Features

UPS topology

Double-conversion (Online)

Output power capacity	2 kVA
Output power	1800 W
Waveform	Pure sine
Input operation voltage (min)	120 V
Input operation voltage (max)	300 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	110 V
Output operation voltage (max)	240 V
Output frequency	47/63 Hz
Output frequency regulation	0 Hz
Output voltage regulation	1%
Response time	0 ms
Power factor	0.99
Crest factor	3:1
Total Harmonic Distortion (THD) (linear load)	3%
Total Harmonic Distortion (THD) (non-linear load)	6%
Noise level	50 dB
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	3 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
RS-232 ports	1
Battery	
Battery capacity	9 Ah
Battery voltage	12 V
Number of battery cells	4
Battery recharge time(90%)	4 h
Design	
Form factor	Rackmount

Product colour	Black
Rack capacity	2U
Cooling type	Active
Built-in fan	Yes
Control type	Buttons
Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 90%
Certificates	
Compliance certificates	CE
Packaging content	
Batteries included	Yes
Cables included	Input power cable, USB cable
Manual	Yes
Weight & dimensions	
Width	438 mm
Depth	410 mm
Height	88 mm
Weight	19 kg
Packaging data	
Software CD	Yes
Logistics data	
Harmonized System (HS) code	85078000
Other features	
Number of phases	1
Packaging content	UPS, Power cable, USB cable, Software on CD, User manual
Sustainability	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

FSP Technology Inc.

Xinpu 6th St. No.101, 330 Taoyuan City, TW

fsplifestyle.com

ATSAKINGAS ASMUO ES

Fortron/Source (Europa) GmbH

Carl-Friedrich-Benz-Strasse 13, D-47877 Willich,

DE

fsplifestyle.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt