



CyberPower OR1000ERM1U uninterruptible power supply (UPS) Line- Interactive 1 kVA 600 W 6 AC outlet(s)



Modelis: OR1000ERM1U

Gamintojas: CYBERPOWER

EAN: 4712856274301

Prekės kodas: 577473

452.99€

Certification: CE, EAC, RCM | Display type: LCD | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | Cable length: 1.83 m | Storage relative humidity (H-H): 0 - 95% | EMI/RFI noise filtering: Yes | Maximum current: 10 A | Weight: 13.7 kg | Response time: 4 ms | AC outlets quantity: 6 AC outlet(s) | Operating relative humidity (H-H): 0 - 95% | Automatic Voltage Regulation (AVR): Yes | Surge protection: Yes | USB port: Yes | Product colour: Silver | Package height: 158 mm | Audible alarm(s): Yes | Rack capacity: 1U | Serial ports quantity: 1 | Output frequency: 50/60 Hz | Modem (RJ-11) ports: 1 | Operating altitude: 0 - 3000 m | Input operation voltage (min): 165 V | Power plug: C14 coupler | Hot-swap battery: Yes | Power protection features: Overload | Number of batteries

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

supported: 1 | Housing material: Metal | Battery recharge time: 8 h | Form factor: Rackmount | Input frequency: 50/60 Hz | Surge energy rating: 810 J | Storage temperature (T-T): -15 - 45 °C | Output power: 600 W | Audible alarm modes: Fault, Low battery alarm, Overload alarm | Waveform: Sine | LED indicators: Operation | Output operation voltage (max): 230 V | UPS topology: Line-Interactive | Width: 433 mm | Power factor: 0.6 | Cables included: USB cable | Input operation voltage (max): 271 V | Package width: 545 mm | Harmonized System (HS) code: 8504408590 | Output power capacity: 1 kVA | Height: 44 mm | Typical backup time at half load: 14 min | Typical backup time at full load: 3.5 min | Non-operating altitude: 0 - 15000 m | Depth: 389 mm | AC outlet types: C13 coupler | Battery technology: Sealed Lead Acid (VRLA) | Output operation voltage (min): 230 V | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Compliance certificates: RoHS