



Ever SINLINE RT XL 3000 Line- Interactive 3 kVA 3000 W 9 AC outlet(s)

Modelis: W/SRTXRT-003K00/00

Gamintojas: EVER

EAN: 5907683603809

Prekės kodas: 577485

1,451.00€

Cold start: Yes | Waveform: Sine | Operating temperature (T-T): 0 - 40 °C | Package height: 247 mm | Battery voltage: 12 V | Cooling type: Active | AC outlets quantity: 9 AC outlet(s) | Weight: 42 kg | Storage relative humidity (H-H): 20 - 95% | Cables included: Input power cable | Number of input phases: 1 | Input operation voltage (min): 178 V | USB 2.0 ports quantity: 1 | Typical backup time at full load: 3 min | Power protection features: Short circuit | LED indicators: Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Input operation voltage (max): 281 V | Number of batteries supported: 8 | Operating relative humidity (H-H): 20 - 80% | Display type: LCD | Manual: Yes | Battery capacity: 7 Ah | Automatic Voltage Regulation (AVR): Yes | Ethernet LAN (RJ-45) ports: 1 | Surge protection: Yes | Output power capacity: 3 kVA | Package width: 547 mm | Rubber feet: Yes | Form factor: Rackmount/Tower | International Protection (IP) code: IP20 | Width: 440 mm | Product colour: Black | Quick installation guide: Yes | Power protection features: Overload | Height: 132 mm | Battery recharge time: 4 h | Maximum current: 16 A | Number of output phases: 1 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Input frequency: 50 Hz | AC outlet types: C19 coupler | Number of phases: 1 | Typical backup time at half load: 7 min | Emergency Power Off (EPO): Yes | Operating altitude: 0 - 1000 m | Power plug: C20 coupler | Output operation voltage (max): 253 V | UPS topology: Line-Interactive | AC outlet types: C13 coupler | Storage temperature (T-T): 0 - 45 °C | Output operation voltage (min): 195 V | Output power: 3000 W | Depth: 630 mm