



**Access Point
TELTONIKA
1xLAN ports
3xAntennas
quantity
TAP400000000**

Modelis: TAP400000000

Gamintojas: TELTONIKA

EAN: 4779051845002

Prekės kodas: 577563

99.99€

The TAP400 is a high-performance Wi-Fi 6 access point designed for SMBs that need fast, efficient wireless coverage and simple centralized management. Experience ultra-fast throughput with the dedicated 2.5 GbE uplink and multi-user efficiency of Wi-Fi 6. The device ensures network continuity and seamless expansion with Fast Roaming and Mesh. All network configuration, monitoring, and troubleshooting can be handled remotely via Teltonika RMS, allowing you to seamlessly reach and control other devices on the network. Upgrade your business to high-performance connectivity that covers every corner.

Summary: Teltonika TAP400. 2.4 GHz, 5 GHz, Maximum data transfer rate: 3000 Mbit/s. Security algorithms: PEAP, WPA2-PSK, WPA-EAP, WPA-PSK, WPA3-SAE, WPA3-EAP, OWE, AES-CCMP, TKIP, EAP-TLS. Ethernet LAN data rates: 100,1000,2500 Mbit/s. Power over Ethernet (PoE). Product colour:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

White. Power consumption (max): 11 W | Vendor Homepage: <https://www.teltonika-networks.com/products/access-points/tap400> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 100/1000/2500 | Fast roaming: Yes | Maximum data transfer rate: 3000 | Maximum data transfer rate (2.4 GHz): 576 | Maximum data transfer rate (5 GHz): 2402 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11k/IEEE 802.11r/IEEE 802.11s/IEEE 802.11v/IEEE 802.11w/IEEE 802.1x/IEEE 802.3/IEEE 802.3af/IEEE 802.3az/IEEE 802.3u | Number of simultaneously connected devices (max): 512 | Virtual LAN features: Tagged VLAN | VLAN support: Yes | Wireless meshing: Yes | Blacklist: Yes | MAC address filtering: Yes | Security algorithms: AES-CCMP/EAP-TLS/OWE/PEAP/TKIP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-EAP/WPA-PSK | Whitelist: Yes | Supported network protocols: TCP, UDP, ICMP, GRE, ESP, RIP, OSPF, BGP, IPsec, IPv4, IPv6, ARP, PPP, HTTP, TTPS | Web-based management: Yes | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | DC voltage range: 44 - 57 | Power consumption (max): 11 | Power over Ethernet (PoE): Yes | Housing material: Plastic,Aluminium | International Protection (IP) code: IP30 | LED indicators: Power | Placement: Ceiling | Product colour: White | Reset button: Yes | Antenna direction type: Omni-directional | Antenna gain level (max): 4.9 | Antenna type: Internal | Antennas quantity: 3 | Built-in processor: Yes | Flash memory: 16 | Internal memory: 512 | Internal memory type: DDR3 | Operating system installed: RutOS | Processor frequency: 1300 | Compliance certificates: CB/CE/EAC/Federal Communications Commission (FCC)/Industry Canada (IC)/RCM/UKCA/WEEE | Depth: 31.4 | Height: 158 | Weight: 285 | Width: 158 | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 50 | Model: TAP400 | Model name: TAP400 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001011 | Unit Calculated Weight: 0.318